

REMEDICATION OF CONTAMINATED MARINE SEDIMENT USING
BENTONITE, KAOLIN AND SAND AS CAPPING MATERIALS

MOHAMMED KABIR ALIYU

A thesis submitted in
fulfillment of the requirement for the award of the
Doctor of Philosophy

Faculty of Civil and Environmental Engineering
Universiti Tun Hussein Onn Malaysia

DECEMBER, 2019

ASSOC. PROF. DR CHAN CHEE MING

DEDICATION

This project is dedicated to the Almighty Allah, the most gracious and the most merciful, maker of all things and to my beloved family for their constant support, encouragement and love throughout this journey.



PTTHM
PERPUSTAKAAN TUNKU TUN AMINAH

ACKNOWLEDGEMENT

In the name of Allah, the Most Beneficent and the Most Merciful. All praise is due to the Almighty Allah for giving me the strengths, guidance and patience in completing this thesis. First and foremost, I would like to express my deepest gratitude to my family for their endless love, patience and prayers throughout my academic pursuits. Thank you for your support, your love and care is well acknowledged. I really appreciate all the kind gestures, motivation and prayers. May Allah reward you all with long life and prosperity.

I would like to express my profound gratitude and indebtedness to my supervisor Prof. Dr. Ahmad Tarmizi Bin Abd Karim for his relentless, intellectual, constructive and valuable suggestions and advices throughout the duration of this research work. I also want to thank him for his motivation and encouragement towards achieving the set objectives of the research title topic. Sir am indeed very grateful, may almighty Allah reward you abundantly, Amin.

My appreciation also goes to my Co – supervisor Assoc. Prof Dr. Chan Chee Ming for her encouragement, valuable suggestions, motivation and advices towards achieving the set objectives of the research study. I am indeed very graceful for all your patience and inputs towards the actualization of this research work. I would like to express my gratitude to the technical staff for their technical guidance and support towards my experimental work in the laboratories at Faculty of Civil and Environmental Engineering University Tun Hussein Onn.

Finally, I would like to express my gratitude to the office of research, innovation and commercialization center (ORICC) Universiti Tun Hussein Onn Malaysia for making my study possible through the support with the research grant (U574). Also I would like to appreciate all those who have directly or indirectly contributed to the accomplishment of this project, especially my friends for their motivation, encouragement and moral support. Thank you so much.

ABSTRACT

There is a growing public concern over the issue of sediment contamination resulting from industrial, municipal wastewater, mining activities, and improper use of chemical fertilizer or pesticides. The conventional treatment of contaminated sediment is dredging, but this treatment is expensive and requires a large area of land for disposal. In situ capping of contaminated sediment is considered as a cheaper technique compared to dredging and efficient treatment technology to immobilize pollutants in sediments on site. In this technique, sediments are capped by placing a layer of inert materials like sand, clean soil, or gravel or active materials like activated carbon, zeolite, or apatite over sediments in order to reduce the risk to the aquatic environment. The objective of this study is to determine the effectiveness of using active materials; bentonite (B), kaolin (K), mixture of bentonite with kaolin (1:1) (BK) as capping materials to block the release of five heavy metals (Pb, Cr, Cu, Cd and Zn) from artificially polluted sediments. The effectiveness of B, K, and BK for preventing the leachability of the trace metals was assessed on a bench-scale laboratory experiment in glass tanks for 90 days, where 1cm thick layer of capping material and sand was placed above the contaminated sediment. The results showed that B and BK reduced the leachability of Pb, Cr, and Cu from the sediments. The results also showed that B and BK could be used as potential capping materials for the remediation of contaminated sites due to their significant entrapping of Pb, Cu, and Cr. The pollutants were released into the overlying water from the contaminated sediment in the following decreasing order; $Cd > Zn > Pb > Cu > Cr$. The adsorption kinetics analysis also showed that the process of adsorption was by chemisorption. This study proved that bentonite and mixture of bentonite with kaolin clays covered with sand could be used as capping materials for in situ treatment of Pb, Cu, Cr, Zn, and Cd for contaminated marine sediment.

ABSTRAK

Masyarakat secara umumnya telah menunjukkan kebimbangan terhadap pencemaran sedimen berpunca daripada pelepasan air sisa industri dan perbandaran, aktiviti perlombongan, dan penyalahgunaan baja kimia, serta racun perosak. Rawatan konvensional sedimen tercemar adalah melalui pengorekan tetapi rawatan ini adalah mahal dan memerlukan ruang yang luas untuk pelupusan. Kaedah pelapisan sedimen tercemar di tapak adalah kaedah yang murah berbanding pengorekan dan rawatan yang efisien untuk menyahaktifkan bahan cemar dalam sedimen. Kaedah ini adalah dengan menghamparkan lapisan pasir, tanah yang bersih atau bahan aktif lain seperti karbon teraktif, zeolit, atau apatit ke atas sedimen bagi mengurangkan risiko terhadap persekitaran akuatik. Objektif kajian ini adalah untuk menentukan keberkesanan penggunaan bahan aktif; bentonit (B), kaolin (K), campuran bentonit dengan kaolin (1:1) (BK) sebagai bahan lapisan bagi menghalang pelepasan lima (5) logam berat (Pb, Cr, Cu, Cd, dan Zn) daripada sedimen tercemar tiruan. Keberkesanan B, K dan juga BK dalam mencegah pelepasan logam terlarut ini diuji melalui ujian di makmal dalam tangki kaca selama 90 hari, dengan lapisan ketebalan bahan pelapis 1 cm dan pasir tersebut dihamparkan atas sedimen yang tercemar. Keputusan menunjukkan B dan BK dapat mengurangkan pelepasan logam Pb, Cr, dan Cu daripada sedimen. Keputusan juga menunjukkan bahawa B dan BK berpotensi digunakan sebagai bahan pelapik sedimen melalui keupayaannya memerangkap Pb, Cu dan Cr. Bahan pencemar dilepaskan daripada lapisan sedimen tercemar dengan turutan menurun; $Cd > Zn > Pb > Cu > Cr$. Analisis penyerapan kinetik juga menunjukkan proses penyerapan adalah melalui *chemisorption*. Kajian ini menunjukkan B dan BK dengan lapisan pasir boleh digunakan sebagai bahan pelapik untuk rawatan sedimen marin tercemar dengan Pb, Cu, Cr, Zn, dan Cd.

TABLE OF CONTENTS

DECLARATION	ii
DEDICATION	iii
ACKNOWLEDGEMENT	iv
ABSTRACT	v
ABSTRAK	vi
TABLE OF CONTENTS	vii
LIST OF TABLES	xiii
LIST OF FIGURES	xvi
LIST OF SYMBOLS AND ABBREVIATIONS	xx
CHAPTER 1 INTRODUCTION	
1.1 Background of the study	1
1.2 Problem statement	5
1.3 Research Objectives	8
1.4 Scope of the Research	8
1.5 Significance of the Research	9
1.6 Organisation of Thesis	10
CHAPTER 2 LITERATURE REVIEW	
2.1 Introduction	12
2.2 Contaminated Sediment Remediation	14
2.2.1 Monitored Natural Recovery	15
2.2.2 Dredging	16
2.2.3 In-Situ Remediation	17
2.3 Heavy metals as marine contaminants	19
2.4 Heavy metals in water, sediments and soil	19
2.5 Effects of heavy metals on public health	22

2.6	Anthropogenic Sources of Heavy Metals in Coastal Sediments	25
2.7	Effects of heavy metals on public health	27
2.8	The occurrence of heavy metals in marine sediments	28
2.9	The effect of salinity on heavy metal mobility of harbour sediments	29
2.10	Adsorption of heavy metals by clay minerals	30
2.10.1	Structure of clays	32
2.11	Investigations of the adsorption properties of various clay minerals	38
2.11.1	Heavy metal removal by the smectite group	32
2.11.1.1	Montmorillonite	39
2.11.1.2	Bentonite	43
2.11.1.3	Heavy metals removal by Kaolinite	46
2.11.1.4	Sand cap	50
2.12	Active capping technology: A new environmental remediation of contaminated sediments	51
2.13	In situ remediation of contaminated sediment	54
2.14	Conventional and Amended Capping	57
2.14.1	Conventional and Amended Capping Background Information	57
2.14.2	Capping Objectives and Approaches	57
2.14.3	Active capping materials	59
2.14.4	The use of active materials in active capping technology	60

2.15	Overview of the usage of active capping materials for In situ remediation of contaminated sediment	61
2.16	A thin-layer cap	68
2.17	The selection of capping material	69
2.18	The seawater	71
2.19	Sequential extractions technique	72
2.20	Risk assessment code (RAC)	75
2.21	Kinetic Studies for Adsorption	76
	2.21.1 Adsorption mechanism	76
	2.21.1.1 Physical adsorption	77
	2.21.1.2 Chemisorption	77
2.22	The study on kinetic models	78
2.23	Summary	82

CHAPTER 3 RESEARCH METHODOLOGY

3.1	Introduction	84
3.2	Physical and chemical tests	88
	3.2.1 Natural moisture content	88
	3.2.2 Loss on ignition	88
	3.2.3 Procedure for measuring pH of soil	89
3.3	Materials Preparation and Characterisation	89
	3.3.1 Dredged marine sediment	89
	3.3.2 Bentonite clay	92
	3.3.3 Kaolin	93
	3.3.4 Sand	94
3.4	X-ray fluorescence (XRF) Analysis	94
3.5	X-ray diffraction (XRD)	95
3.6	Cation Exchange Capacity Using Methylene blue Dye Titration	95
3.7	Specific surface area measurements using methylene blue absorption technique	96
3.8	Sediment digestion according to USEPA Method 3050B	97

3.9	Sediment contamination by spiking	98
3.10	Preparation of synthetic sea water	99
3.11	The capping experimental set up	99
3.12	The diagram of the capping experiment	102
3.13	Sequential extraction procedure (SEP)	104
3.14	The BCR three stage sequential extraction procedure	105
3.15	Risk assessment code (RAC)	106
3.16	Kinetic study for adsorption of heavy metals from the marine sediments	107

CHAPTER 4 RESULTS AND DISCUSSIONS

4.1	Introduction	109
4.2	Characteristics of Kuala Perlis sediment	109
4.3	Characteristics of the capping materials	111
4.4	Heavy metal concentration in the sediments before and after spiking	114
4.5	The XRD analysis of the sediment, bentonite, kaolin, and sand	114
4.6	Release of Pb, Cd, Cu, Cr & Zn from the contaminated sediment to the overlying water column	118
4.7	The effect of capping materials to pH increase on the release of trace metals from sediments	123
4.8	Sequential extraction of the trace metals	125
4.9	Risk Assessment Code	133
4.10	Kinetic Studies	137
4.10.1	Kinetic study for adsorption of lead	

	(Pb) on bentonite (B), kaolin (K) and bentonite + kaolin (BK)	137
4.10.2	Kinetic study for adsorption of Copper (Cu) on bentonite, kaolin and bentonite + kaolin	140
4.10.3	Kinetic study for the adsorption of chromium (Cr) on Bentonite, kaolin, and Bentonite+Kaolin	142
4.10.4	Kinetic study for adsorption of Cadmium (Cd) on bentonite, kaolin and bentonite + kaolin	144
4.10.5	Kinetic study for adsorption of Zinc (Zn) on bentonite, kaolin and bentonite + kaolin	147
4.11	Summary	149
CHAPTER 5 CONCLUSION AND RECOMMENDATION		
5.1	Introduction	151
5.2	Conclusion	151
5.3	Recommendations	153
REFERENCES		155
APPENDICES		197
APPENDIX A The equipments used in the experiment		197
APPENDIX B		202
Calculations for the quantity of each heavy metal spiked		202
APPENDIX C		205
The result for the release of trace metals from the contaminated sediments to overlying sea water over the course of 90 days.		205
APPENDIX D		209
APPENDIX E		218
Sequential extraction results		218

APPENDIX F	221
Sequential extraction results for Pb, Cr, Cu, Cd and Zn in the four fractions (Raw data)	221
APPENDIX G	231
APPENDIX H	241
The concentration of the released heavy metals in the uncapped and capped sediments over 90 days period (Raw data)	241
APPENDIX I	249
The release concentration of Pb, Cr, Cu, Cd and Zn from day 2 to 90 days	249

LIST OF PUBLICATIONS

VITA

257



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF TABLES

2.1	Sources and health effects of various toxic metals	23
2.2	Sediment Quality Guidelines for heavy metals.....	26
2.3	Comparison between passive capping and active capping technology (Zhang <i>et al.</i> , 2016)	60
2.4	Overview of active/non active materials used in active capping laboratory studies	66
2.5	The Salinity of some naturally saline waters	
	(Source: Clean Water Team (CWT) 2004)	71
2.6	Synthetic Seawater ASTM D1141-98 (Original Standard ASTM D1141-52)	71
2.7	The BCR three-stage sequential extraction scheme.....	74
2.8	Risk assessment code	75
3.1	The quantities of each heavy metal spiked on the sediment	99
4.1	Characteristics and background concentration of metals in the sediment	110
4.2	Standard guideline applicable for heavy metals in marine sediment.....	110
4.3	The chemical composition of the dredged marine sediment.....	111
4.4	Chemical composition and physical properties of Bentonite, Kaolin, and sand used as capping materials.....	112
4.5	The sediment quality guidelines for Heavy metals	113
4.6	The recovered concentrations of the heavy metals after spiking	114
4.7	The average heavy metal concentration in the seawater overlying the contaminated sediments capped with bentonite, kaolin, and mixture of bentonite with kaolin during 90 days.....	119
4.8	Risk assessment code for Pb in the upper sediment layer.....	133
4.9	Risk assessment code for Pb in the bottom sediment layer	134
4.10	Risk assessment code for Cr in the upper sediment layer.....	134

4.11	Risk assessment code for Cr in the bottom sediment layer.....	134
4.12	Risk assessment code for Cu in the upper sediment layer	135
4.13	Risk assessment code for Cu in the bottom sediment layer	135
4.14	Risk assessment code for Cd in the upper sediment layer	135
4.15	Risk assessment code for Cd in the bottom sediment layer	136
4.16	Risk assessment code for Zn in the upper sediment layer	136
4.17	Risk assessment code for Zn in the bottom sediment layer	136
4.18	Correlation coefficient (R^2) and standard error of estimate (SE) of the various kinetic equations for Pb sorption.....	140
4.19	Correlation coefficient (R^2) and standard error of estimate (SE) of the various kinetic equations for Cu sorption.	142
4.20	Correlation coefficient (R^2) and standard error of estimate (SE) of the various kinetic equations for Cr sorption.....	144
4.21	Correlation coefficient (R^2) and standard error of estimate (SE) of the various kinetic equations for Cd sorption	147
4.22	Correlation coefficient (R^2) and standard error of estimate (SE) of the various kinetic equations for Zn sorption	149
C.1	Concentration of trace metals at 2, 4, 6 & 7 days	205
C.2	Concentration of trace metals at 14, 21, 28 & 35 days	206
C.3	Concentration of trace metals at 42, 49, 56 & 63 days	207
C.4	Concentration of trace metals at 70, 77, 84 & 90 days	208
D.1	The pH, EC and D.O of the overlying sea water monitored over the period of 90 days	209
E.1	Concentrations of Pb in the four geochemical fractions in the upper layer sediment	218
E.2	Concentrations of Pb in the four geochemical fractions in the bottom layer sediment	218
E.3	Concentrations of Cr in the four geochemical fractions in the upper layer sediment	218
E.4	Concentrations of Cr in the four geochemical fractions in the bottom layer sediment	219
E.5	Concentrations of Cu in the four geochemical fractions in the upper layer sediment	219

E.6	Concentrations of Cu in the four geochemical fractions in the bottom layer sediment	219
E.7	Concentrations of Cd in the four geochemical fractions in the upper layer sediment	219
E.8	Concentrations of Cd in the four geochemical fractions in the bottom layer sediment	220
E.9	Concentrations of Zn in the four geochemical fractions in the upper layer sediment	220
E.10	Concentrations of Zn in the four geochemical fractions in the bottom layer sediment	220
	Kinetic adsorption parameters for Pb, Cr, Cu, Cd and Zn on Bentonite (Sed+B+S), Kaolin (Sed+K+S) and Bentonite+Kaolin (Sed+B+K+S). 231	



LIST OF FIGURES

2.1	Technologies included in USEPA Records of Decision (Mohan <i>et al.</i> , 2016)	15
2.2	Kaolinite (1:1)	34
2.3	Montmorillonite (Smectite) layers structure	35
2.4	Vermiculite layers structure	36
2.5	Illite layers structure	37
2.6	Chlorite layers structure	38
3.1	Stage I and stage II illustrating the sample collection and material characterization	86
3.2	The flow chart illustrating capping experiment and testing.	87
3.3	The flow chart (Results & Conclusions)	88
3.4	The satellite image of the dredging location where sediment samples was taken at Kuala Perlis estuary, Malaysia	90
3.5	Backhoe Dredger	91
3.6	The wet dredged marine sediment	91
3.7	The dried dredged marine sediment after sieving	92
3.8	Bentonite	93
3.9	kaolin	93
3.10	sieved sand	94
3.11	Schematic diagram of experimental conditions regarding depth of the capping materials, sediment and sand,	101
3.12	Sediment capping experimental set up: A is the contaminated sediment without any capping (Control), B is sediment capped with bentonite and sand (Sed+B+S), while C is sediment capped with kaolin and sand (Sed+K+S) and D is sediment capped with composite (50:50) of bentonite with kaolin and sand	101
3.13	Front view image of the control (without capping layer) sample	102

3.14	Front view image of the bentonite + sand capping layer	102
3.15	Front view image of the kaolin + sand capping layer	103
3.16	Front view image of the kaolin + bentonite (50:50) + sand capping	103
4.1	X-ray diffraction pattern of the marine sediment	115
4.2	X-ray diffraction pattern of Bentonite clay	116
4.3	X-ray diffraction pattern of the sand	117
4.4	X-ray diffraction patterns of the Kaolin clay	117
4.5	Release of Pb, Cu, Cr, Cd and Zn from control sample for 90 days period	120
4.6	Release of Pb, Cu, Cr, Cd and Zn from bentonite + sand sample for 90 days period	120
4.7	Release of Pb, Cu, Cr, Cd and Zn from kaolin + sand capping layer for 90 days period	121
4.8	Release of Pb, Cu, Cr, Cd and Zn from (bentonite + kaolin) + sand capping layer for 90 days period	121
4.9	(A) pH and (B) electrical conductivity (EC) of the seawater above the uncapped sediments and those capped with bentonite, kaolin and mixture of bentonite + kaolin respectively through out 90 days period	124
4.10	Fraction of Cd in the upper sediment layer obtained 0 - 1 cm below the capping layer	127
4.11	Fraction of Cd in the bottom sediment layer obtained 1 - 2 cm below the capping layer	127
4.12	Fraction of Zn in the upper sediment layer obtained 0 - 1 cm below the capping layer	128
4.13	Fraction of Zn in the bottom sediment layer obtained 1 - 2 cm below the capping layer	128
4.14	Fraction of Cr in the upper sediment layer obtained 0 - 1 cm below the capping layer	129
4.15	Fraction of Cr in the bottom sediment layer obtained 1 - 2 cm below the capping layer	129
4.16	Fraction of Pb in the upper sediment layer obtained 0 - 1 cm below the capping layer	130

4.17	Fraction of Pb in the bottom sediment layer obtained 1 - 2 cm below the capping layer	130
4.18	Fraction of Cu in the upper sediment layer obtained 0 - 1 cm below the capping layer	131
4.19	Fraction of Cu in the bottom sediment layer obtained 1 - 2 cm below the capping layer	132
4.20	A plot of Elovich equation for Pb sorption on Sed+B+S, Sed+K+S and Sed +(B+K)+S capping treatments	138
4.21	A plot of Second-order equation for Pb sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	138
4.22	A plot of Two – constant rate equation for Pb sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	139
4.23	A plot of Elovich equation for Cu sorption on Sed+B+S, Sed+K+S and Sed + (B+K) +S capping treatments	141
4.24	A plot of Second-order equation for Cu sorption on Sed+B+S, Sed+K+S and Sed + (B+K)+S capping treatments	141
4.25	A plot of Two – constant rate equation for Cu sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	141
4.26	A plot of Elovich equation for Cr sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	143
4.27	A plot of Second-order equation for Cr sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	143
4.28	A plot of Two – constant rate equation for Cr sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	143
4.29	A plot of Elovich equation for Cd sorption on Sed+B+S, Sed+K+S, and Sed+(B+K)+S capping treatments.	145
4.30	A plot of Second-order equation for Cd sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	145
4.31	A plot of Two – constant rate equation for Cd sorption on Sed+B+S, Sed+K+S, and Sed+(B+K)+S capping treatments.	146
4.32	A plot of Elovich equation for Zn sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments.	147

4.33	A plot of Second-order equation for Zn sorption on Sed+B+S, Sed+K+S, and Sed+(B+K)+S capping treatments.	148
4.34	A plot of Two – constant rate equation for Zn sorption on Sed+B+S, Sed+K+S and Sed+(B+K)+S capping treatments	148
	The pH/EC meter (HQ 440D multi, Hatch, USA)	197
	Inductively coupled plasma optical emission spectrometry (ICP-OES)	197
	X-ray diffraction equipment (D8 Advance, Bruker, Germany)	198
	X-ray Fluorescence machine (S4 Pioneer, Bruker aXS Germany)	198
	The In situ capping experimental set up	199
	Tachometre for measuring rpm	199
	Dissolved oxygen metre	200
	Plastic syringe conneted with rubber tube	200
	Side view image of the experimental model	201
	Upper view image of the experimental set up	201
	Release of Pb, Cd, Cr, Cu and Zn at day 2	249
	Release of Pb, Cd, Cr, Cu and Zn at day 4	249
	Release of Pb, Cd, Cr, Cu and Zn at day 6	250
	Release of Pb, Cd, Cr, Cu and Zn at day 7	250
	Release of Pb, Cd, Cr, Cu and Zn at day 14	251
	Release of Pb, Cd, Cr, Cu and Zn at day 21	251
	Release of Pb, Cd, Cr, Cu and Zn at day 28	252
	Release of Pb, Cd, Cr, Cu and Zn at day 35	252
	Release of Pb, Cd, Cr, Cu and Zn at day 42	253
	Release of Pb, Cd, Cr, Cu and Zn at day 49	253
	Release of Pb, Cd, Cr, Cu and Zn at day 56	254
	Release of Pb, Cd, Cr, Cu and Zn at day 63	254
	Release of Pb, Cd, Cr, Cu and Zn at day 70	255
	Release of Pb, Cd, Cr, Cu and Zn at day 77	255
	Release of Pb, Cd, Cr, Cu and Zn at day 84	256
	Release of Pb, Cd, Cr, Cu and Zn at day 90	256

LIST OF SYMBOLS AND ABBREVIATIONS

MNR	Monitored natural recovery
Rpm	Revolution per minute
Pb	Lead
Cd	Cadmium
Cu	Copper
Cr	Chromium
Zn	Zinc
AAS	Atomic absorption spectrometer
ICP-MS	Inductively Coupled Plasma Mass Spectroscopy
ICP-OES	Inductively coupled plasma optical emission spectrometre
Sed+B+S	Sediment + bentonite + sand
Sed+K+S	Sediment + kaolin + sand
Sed+(B+K)+S	Sediment + (bentonite + kaolin) + sand
XRF	X ray fluorescence
XRD	X ray diffraction
CEC	Cation exchange capacity
USEPA	United states environmental protection agency
EC	Electrical conductivity
B	Bentonite
K	Kaolin
BK	Bentonite + Kaolin
RAC	Risk assessment code
AAS	Atomic adsorption spectroscopy
C_o	Initial concentration of pollutant before treatment
C_t	Concentration of pollutant released into water column
T	time (number of days)
NR	No risk
LR	Low risk
MR	Medium risk

D.O	Dissolve oxygen
MMT	monmorillonite
USCS	Unified Soil Classification System
MH	Plasticity silt
Mg/L	milligram per litre
HR	High risk
VHR	very high risk
F1	Exchangeable fraction in the sequential extraction
F2	Reducible fraction in the sequential extraction
F3	Oxidisable fraction in the sequential extraction
F4	Residual fraction in the sequential extraction
ISC	Insitu capping
%	Percentage
ppm	Parts per million
UTHM	Universiti Tun Hussein Onn Malaysia



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

CHAPTER 1

INTRODUCTION

1.1 Background of the study

Remediation of contaminated sediments is one of the most difficult and challenging problems in environmental engineering today. One of the primary risks associated with contaminated sediments is bioaccumulation in benthic organisms, which is a route of entry into the food chain. Thus an important goal of sediment remediation is reducing concentrations to these organisms (Lampert & Reible, 2009). Presently, due to the regular contamination of the marine sediments by the municipal and industrial waste discharge, improper use of chemical fertilizer and pesticides, waste water irrigation and mining activities, a public concern has been aroused over the issue (Zeng *et al.*, 2013a; Awad *et al.*, 2014; Teng *et al.*, 2014; Tang *et al.*, 2015). Contamination of marine sediments poses a potential threat to marine resources and human health through consumption of seafood. Marine sediments are exposed to a wide range of potential contamination by chemicals that tend to sorb to fine-grained particles. Heavy metals and organic pollutants are the two major kinds of pollutants found in sediment (Zhang *et al.*, 2014; Zeng *et al.*, 2016; Zhang *et al.*, 2016b; Liu *et al.*, 2016; Song *et al.*, 2017). And these are toxic contaminants, posing a great risk to the safety of food, ecological environment and human health. The problem of contamination of marine sediment is widespread in coastal water in many parts of the world. The predominant mode of heavy metal retention in sediments can be significantly influenced by the level of sediments contamination by the metal, in addition to geochemical factors and behaviours of the metal itself, metal particles frequently bind with the sediments and do not easily dissolve or migrate with water.

Several attempts have been made to find a solution to the problem of sediment contamination. So various methods and strategies have been implemented for the control and reduction of the pollution (Peng *et al.*, 2009; Gerhardt *et al.*, 2009; Xu *et al.*, 2012; Cheng *et al.*, 2016a; Zhang *et al.*, 2013a). In general, the remediation technologies can be grouped into two major strategies: in situ and ex situ remediation. In situ remediation is the treatment of the pollutant on-site, which means at the original place of contamination. This plan is targeted at the removal of the pollutant from sediment or soil without moving the sediment or soil itself. Ex-situ remediation involves excavation and treating the contaminated sediment or soil at someplace away from the site. Assessing these two strategies, in situ remediations propose several potential economic, technical, and environmental advantages (Bardos *et al.*, 2000; Kuppusamy *et al.*, 2016). In some instances, when considering the size of the contaminated area and the cost-effectiveness, in situ remediation is the only means of pollutant removal. Globally accepted technologies for sediment remediation generally rely on either removing the contaminated sediment, then managing it ex-situ or remediating sediment contamination in-place (in-situ). In-situ capping is an internationally recognized and accepted technology for remediating contaminated sediments and is extensively used in other countries like the USA and Norway.

For a large scale of contaminated sediment, in situ remediation brings about less disturbance to the ecosystem, the operation is comparatively easy, and the cost is more inexpensive than the ex situ treatment (Carberry and Wik, 2001; Guiwei *et al.*, 2008; Velimirovic *et al.*, 2014). Capping contaminated sediments is an in situ remediation method where by a capping material is laid on top of contaminated sediments to inhibit the constant contamination of surface water and biota on top of the contaminated sediments. It involves the placing of a subaqueous cover over contaminated sediments to stabilize sediments, minimize their re-suspension and transport, and reduce dissolved contaminant transport into surface waters. It is an applicable technology which limits the release of contaminants present in the sediments by binding or adsorption, which can keep the concentration of contaminants in the overlaying water at a safe level (Gomes *et al.*, 2013, Gosh *et al.*, 2011). In addition, capping treatment has less interference to the aquatic ecosystem compared to other sediment remediation technologies (Gosh *et al.*, 2011,

Beckingham *et al.*, 2013). Dredging and disposal are costly and may possibly bring about secondary contamination by disturbed sediments in the course of the dredging process (Nayar *et al.*, 2004; Knox *et al.*, 2008). Capping is assumed to be much inexpensive than dredging, and it is thought to be very effective at obstructing the diffusion of contaminants (Föstner & Apitz 2007; Perelo 2010; Sun *et al.* 2010).

Presently, materials including clay, gravel, zeolites, and activated carbon are widely applied in capping treatment methods (Jacobs & Förstner, 1999, Fadaei *et al.*, 2015). Investigation has been done on capping materials that can be used to contain inorganic contaminants, and on various capping materials used for every contaminant. Inorganic contaminants, specifically heavy metals such as Ni, Cd, Zn and Pb have been described to be successfully immobilized by phosphate minerals, including calcium phytate (Knox *et al.*, 2008), apatite (Knox *et al.*, 2006; Knox *et al.*, 2008) and mineral rock phosphate (Basta and McGowen 2004; Knox *et al.*, 2008). More natural minerals such as limestone and zeolite were as well used as a capping material to impede the release of heavy metals (Jacobs & Förstner 1999; Eek *et al.*, 2007; Knox *et al.*, 2008). In addition to heavy metals, nitrogen and phosphorus release were also stopped by calcium and zeolite minerals (Huang *et al.*, 2011; Lin *et al.*, 2011; Yin *et al.*, 2013). Even though several materials have been evaluated as potential capping materials, additional research is required on low-cost and affordable material for in situ remediation of contaminated sediments.

Bentonite, a 2:1 type of aluminosilicate, is a kind of expandable clay composed primarily of montmorillonite, characterized by high permanent negative charges and large specific surface area. It has been documented that bentonite is an efficient adsorbent for some heavy metals (Karapinar and Donat, 2009; Hamidpour *et al.*, 2010; Li *et al.*, 2010).

Sediment caps incorporating certain clays, like bentonite can: (a) create a hydraulic barrier that can effectively divert flow of contaminated sediment porewaters away from migrating through the cap; (b) reduce the rate of advective transport of dissolved contaminants up into and through the cap; and (c) reduce steady-state contaminant flux through the cap more effectively than can coarser-grained materials, like sand (Reible and Lampert, 2014; USEPA, 2007; USEPA, 2013; Reible, 2008; Anchor QEA and SAO, 2014). It has been well accepted that heavy metal contaminants are retained by clayey soils through three main

mechanisms: adsorption, surface precipitation and chemical bonding (Bradl, 2004; Sposito, 2008). Bentonite, as a low-cost and efficient adsorbent, has great potential in application for removing heavy metals from sediments because of its abundance, chemical and mechanical stability, high adsorption capability and unique structural properties (Shi *et al.*, 2011). Removal of metal ions using bentonite is based on ion exchange and adsorption mechanisms because of the relatively high cation exchange capacity (CEC) and specific surface area of bentonite (Shi *et al.*, 2011).

Similarly the removal of metal ions using kaolinite clay is also based on ion exchange and adsorption mechanisms (Tomašević *et al.*, 2014) and kaolinite has a relative low cation-exchange capacity (CEC) [3–15 meq/100 g of clay] and smaller surface area ranged from 10 to 20 m²/g (Suraj *et al.*, 1998). A number of studies concerning kaolinite clay used to remove heavy metals from aqueous solution have been reported. Recently, kaolinite clay used to remove Pb (II), Cd (II) and Ni(II) in aqueous medium has been investigated through the process of adsorption under a set of variables (Gupta & Bhattacharya, 2008). Similarly, kaolinite has been used as adsorbents for the removal of Fe(III), Co(II) and Ni(II) in aqueous medium (Bhattacharya & Gupta, 2013) and for removal of Cu(II) (Bhattacharya & Gupta, 2006) and Pb(II) (Gupta & Bhattacharya, 2005). At the moment, there is not enough data about in situ capping treatments of contaminated marine sediments using bentonite and kaolin.

Although many researchers have investigated the application of reactive capping for the sediments contaminated with nutrients and organic matters, few types of research on heavy metals in the sediments have been performed. Knowledge of the application of in situ cappings for sediments contaminated with heavy metals is insufficient (Akcil, 2015). This study aims to evaluate the effectiveness of using bentonite clay, kaolin, and sand as capping materials to prevent the release of trace metals (Pb, Cd, Cr, Zn, and Cu) from the spiked heavily contaminated marine sediment (3000 ppm). To the best of our understanding, these materials have not been used as active capping material for treating contaminated marine sediment by other researchers. Although most of the previous researches were run in batch experimental condition with no flows, which has drawbacks in field usages and small number of studies were done in a flow condition, all the tests in this study were made under a flow situation using a glass tank, and to simulate ocean wave an impeller was

REFERENCES

- Abollino, O., Aceto, M., Malandrino, M., Sarzanini, C., & Mentasti, E. (2003). Adsorption of heavy metals on Na-montmorillonite. Effect of pH and organic substances. *Water research*, 37(7), 1619-1627.
- Abou-El-Sherbini, K. S., & Hassanien, M. M. (2010). Study of organically-modified montmorillonite clay for the removal of copper (II). *Journal of hazardous materials*, 184(1-3), 654-661.
- Adepoju-Bello, A. A., & Alabi, O. M. (2005). Heavy metals: A review. *The Nig. J. Pharm*, 37, 41-45.
- Agnello, A. C., Bagard, M., Van Hullebusch, E. D., Esposito, G., & Huguenot, D. (2016). Comparative bioremediation of heavy metals and petroleum hydrocarbons co-contaminated soil by natural attenuation, phytoremediation, bioaugmentation and bioaugmentation-assisted phytoremediation. *Science of the Total Environment*, 563, 693-703.
- Aharoni, C., & Sparks, D. L. (1991). Kinetics of soil chemical reactions a theoretical treatment. *Rates of soil chemical processes*, (ratesofsoilchem), 1-18.
- Aharoni, C., & Tompkins, F. C. (1970). Kinetics of adsorption and desorption and the Elovich equation. In *Advances in catalysis* (Vol. 21, pp. 1-49). Academic Press.
- Ahmad, A. A., & Hameed, B. H. (2010). Fixed-bed adsorption of reactive azo dye onto granular activated carbon prepared from waste. *Journal of hazardous materials*, 175(1), 298-303.
- Akafia, M. M., Reich, T. J., & Koretsky, C. M. (2011). Assessing Cd, Co, Cu, Ni, and Pb Sorption on montmorillonite using surface complexation models. *Applied geochemistry*, 26, S154-S157.
- Akan, J. C., Abdulrahman, F. I., Sodipo, O. A., Ochanya, A. E., & Askira, Y. K. (2010). Heavy metals in sediments from River Ngada, Maiduguri

- Metropolis, Borno State, Nigeria. *Journal of Environmental Chemistry and Ecotoxicology*, 2(9), 131-140.
- Akcil, A., Erust, C., Ozdemiroglu, S., Fonti, V., & Beolchini, F. (2015). A review of approaches and techniques used in aquatic contaminated sediments: metal removal and stabilization by chemical and biotechnological processes. *Journal of Cleaner Production*, 86, 24-36.
- Ali, H., Khan, E., & Sajad, M. A. (2013). Phytoremediation of heavy metals concepts and applications. *Chemosphere*, 91(7), 869-881.
- Al-Jlil, S. A. (2015). Kinetic of Adsorption of Chromium and Lead Ions on Bentonite Clay Using Novel Internal Parallel Model. *Research Journal of Environmental Toxicology*, 9(1), 1.
- Alvarez EA, Mochón MC, Jiménez Sánchez JC, Ternero Rodríguez M (2002) Heavy metal extractable forms in sludge from wastewater treatment plants. *Chemosphere* 47: 765-775.
- Amer, M. W., Khalili, F. I., & Awwad, A. M. (2010). Adsorption of lead, zinc and cadmium ions on polyphosphate-modified kaolinite clay. *Journal of Environmental Chemistry and Ecotoxicology*, 2(1), 001-008.
- Anchor QEA and SAO Environmental Consulting AB (SAO). (2014). Modeled Performance of Active Versus Passive Sediment Caps. Available upon request from SAO, www.saoec.se.
- Anglin-Brown B, Armour-Brown A, Lalor GC (1995) Heavy metal pollution in Jamaica 1: Survey of cadmium, lead and zinc concentrations in the Kintyre and hope flat districts. *Environ Geochem Health* 17: 51-56.
- Anirudhan, T. S., & Radhakrishnan, P. G. (2007). Chromium (III) removal from water and wastewater using a carboxylate-functionalized cation exchanger prepared from a lignocellulosic residue. *Journal of Colloid and Interface Science*, 316(2), 268-276.
- Ansari, A.A., Gill, S.S., Gill, R., Lanza, R.G., Newman, L., (2015). Phytoremediation: Management of Environmental Contaminants. Vol. 1 Springer International Publishing, Cham.
- Antizar-Ladislao, B. (2008). Environmental levels, toxicity and human exposure to tributyltin (TBT)-contaminated marine environment. A review. *Environment international*, 34(2), 292-308.

- Apitz SE, Power EA (2002) From risk assessment to sediment management an international perspective. *J Soils Sediments* 2:61–66.
- Arfaoui, S., Frini-Srasra, N., & Srasra, E. (2008). Modelling of the adsorption of the chromium ion by modified clays. *Desalination*, 222(1-3), 474-481.
- Arvand, M., & Pakseresht, M. A. (2013). Cadmium adsorption on modified chitosan-coated bentonite: batch experimental studies. *Journal of Chemical Technology & Biotechnology*, 88(4), 572-578.
- Ashraf MA, Maah MJ, Yuso I (2012). Chemical Speciation and potential mobility of heavy metals in the soil of former tin mining catchment. *The Scientific World Journal*, 10: 1-11.
- Atkinson, C. J., Fitzgerald, J. D., & Hipps, N. A. (2010). Potential mechanisms for achieving agricultural benefits from biochar application to temperate soils: a review. *Plant and soil*, 337(1-2), 1-18.
- ATSDR (1994) US Department of Health and Human Service, Toxicological profile for zinc. US Department of Health and Human Service, Public Health Service 205: 88–608.
- ATSDR, (2000) Agency for Toxic Substances and Disease Registry, Atlanta, Toxicological Profile for Chromium. GA: U.S. Department of Health and Human Service, Public Health Service. 1600 Clifton Road N.E, E-29 Atlanta, Georgia. 30333(6-9) 95 - 134.
- Awad, Y.M., Kim, S.C., Abd El-Azeem, S.A.M., Kim, K.H., Kim, K.R., Kim, K., et al., 2014. Veterinary antibiotics contamination in water, sediment, and soil near a swine manure composting facility. *Environmental Earth Sciences* 71 (3), 1433–1440.
- Awan AM, Baigl MA, Igbal J, Aslam MR, Ijaz N (2003) Recovery of chromate form tannery waste water. *Electron. J. Environ. Agric. Food Chem* 2: 543–548.
- Azcue JM, Zeman AJ, Forstner U (1998a) International review of application of subaqueous capping techniques for remediation of contaminated sediments. *Environmental Geotechnics*, Vols 1–4. A a Balkema Publishers, Leiden
- Azcue JM, Zeman AJ, Mudroch A, Rosa F, Patterson T (1998b) Assessment of sediment and porewater after one year of subaqueous capping of

- contaminated sediments in Hamilton Harbour, Canada. *Water Sci Technol* 37:323–329.
- Aziz, B. K., & Shareef, F. H. (2013). Using Natural Clays and Spent Bleaching Clay as Cheap Adsorbent for the Removal of Phenol in Aqueous Media. *International Journal of Basic and Applied Sciences*, 88-93.
- Bardos, R. P., Morgan, P., & Swannell, R. P. (2000). Application of in situ Remediation. *Land Contamination & Reclamation*, 8(4), 4.
- Bardos, R. P., Morgan, P., & Swannell, R. P. (2000). Application of in situ Remediation. *Land Contamination & Reclamation*, 8(4), 4.
- Barkat, M., Chegrouche, S., Mellah, A., Bensmain, B., Nibou, D., & Boufatit, M. (2014). Application of algerian bentonite in the removal of cadmium (II) and chromium (VI) from aqueous solutions. *Journal of Surface Engineered Materials and Advanced Technology*, 4(04), 210.
- Bar-on, P. and Shainberg, I. (1970) Hydrolysis and decomposition of Na-montmorillonite in distilled water. *Soil Science*, 109, 241-246.
- Barth, E. F., Reible, D., & Bullard, A. (2008). Evaluation of the physical stability, groundwater seepage control, and faunal changes associated with an AquaBlok® sediment cap. *Remediation Journal: The Journal of Environmental Cleanup Costs, Technologies & Techniques*, 18(4), 63-70.
- Bates, R. L., & Jackson, J. A. (1987). Glossary of Geology: American Geological Institute. *Alexandria, Virginia*, 788. pp. 65, 123, 262, 432
- Beckingham, B., Buys, D., Vandewalker, H., & Ghosh, U. (2013). Observations of limited secondary effects to benthic invertebrates and macrophytes with activated carbon amendment in river sediments. *Environmental toxicology and chemistry*, 32(7), 1504-1515.
- Beckingham, B., Buys, D., Vandewalker, H., & Ghosh, U. (2013). Observations of limited secondary effects to benthic invertebrates and macrophytes with activated carbon amendment in river sediments. *Environmental toxicology and chemistry*, 32(7), 1504-1515.
- Begum, Z. A., Rahman, I. M., Tate, Y., Sawai, H., Maki, T., & Hasegawa, H. (2012). Remediation of toxic metal contaminated soil by washing with biodegradable aminopolycarboxylate chelants. *Chemosphere*, 87(10), 1161-1170..

- Belin, S, Sany, S. B. T., Salleh, A., Rezayi, M., Saadati, N., Narimany, L., & Tehrani, G. M. (2013). Distribution and contamination of heavy metal in the coastal sediments of Port Klang, Selangor, Malaysia. *Water, Air, & Soil Pollution*, 224(4), 1476.
- Bellir, K., Lehocine, M. B., & Meniai, A. H. (2013). Zinc removal from aqueous solutions by adsorption onto bentonite. *Desalination and Water Treatment*, 51(25-27), 5035-5048.
- Benitez, L. N., & Dubois, J. P. (1999). Evaluation of the selectivity of sequential extraction procedures applied to the speciation of cadmium in soils. *International Journal of Environmental Analytical Chemistry*, 74(1-4), 289-303.
- Berg U, Neumann T, Donnert D, Nüesch R, Stüben D (2004) Sediment capping in eutrophic lakes—efficiency of undisturbed calcite barriers to immobilize phosphorus. *Appl Geochem* 19:1759–1771.
- Bhattacharyya, K. G., & Gupta, S. S. (2006). Adsorption of Fe (III) from water by natural and acid activated clays: studies on equilibrium isotherm, kinetics and thermodynamics of interactions. *Adsorption*, 12(3), 185-204.
- Bhattacharyya, K. G., & Gupta, S. S. (2006). Kaolinite, montmorillonite, and their modified derivatives as adsorbents for removal of Cu (II) from aqueous solution. *Separation and Purification Technology*, 50(3), 388-397.
- Bhattacharyya, K. G., & Gupta, S. S. (2007). Adsorption of Co (II) from aqueous medium on natural and acid activated kaolinite and montmorillonite. *Separation Science and Technology*, 42(15), 3391-3418.
- Bhattacharyya, K. G., & Gupta, S. S. (2008). Kaolinite and montmorillonite as adsorbents for Fe (III), Co (II) and Ni (II) in aqueous medium. *Applied Clay Science*, 41(1-2), 1-9.
- Bhattacharyya, K. G., & Gupta, S. S. (2009). Adsorptive accumulation of Cd (II), Co (II), Cu (II), Pb (II) and Ni (II) ions from water onto kaolinite: influence of acid activation. *Adsorption Science & Technology*, 27(1), 47-68.
- Bhattacharyya, K. G., & Sen Gupta, S. (2006). Adsorption of chromium (VI) from water by clays. *Industrial & engineering chemistry research*, 45(21), 7232-7240.

- Bocos, E., Fernández-Costas, C., Pazos, M., & Sanromán, M. Á. (2015). Removal of PAHs and pesticides from polluted soils by enhanced electrokinetic-Fenton treatment. *Chemosphere*, 125, 168-174.
- Bokuniewicz, H. J. (1997). Contaminated Sediments in Ports and Waterways-Cleanup Strategies and Technologies. National Research Council prepared by Committee on Contaminated Marine Sediments.
- Bradl, H. B. (2004). Adsorption of heavy metal ions on soils and soils constituents. *Journal of colloid and interface science*, 277(1), 1-18.
- Bradshaw, M. J. (1975). Origin of montmorillonite bands in the Middle Jurassic of eastern England. *Earth and Planetary Science Letters*, 26(2), 245-252.
- Bradshaw, M. J. (1975). Origin of montmorillonite bands in the Middle Jurassic of eastern England. *Earth and Planetary Science Letters*, 26(2), 245-252.
- Brenner, R. C., Magar, V. S., Ickes, J. A., Foote, E. A., Abbott, J. E., Bingler, L. S., & Crecelius, E. A. (2004). Long-term recovery of PCB-contaminated surface sediments at the Sangamo-Weston/Twelvemile Creek/Lake Hartwell Superfund site. *Environmental science & technology*, 38(8), 2328-2337.
- Bridges TS, Apitz SE, Evison L, Keckler K, Logan M, Nadeau S, Wenning RJ (2006) Risk-based decision making to manage contaminated sediments. *Integr Environ Assess Manag* 2:51–58.
- Bridges, T. S., S. Ells, D. Hayes, D. Mount, S. C. Nadeau, M. R. Palermo, C. Patmont and P. Schroeder (2008). the four rs of Environmental dredging: resuspension, release, residual, and risk, DTIC Document.
- Brigatti, M. F., Galan, E., & Theng, B. K. G. (2013). Structure and mineralogy of clay minerals. In *Developments in clay science* (Vol. 5, pp. 21-81). Elsevier.
- Buccolieri, A., Buccolieri, G., Cardellicchio, N., Dell'Atti, A., Di Leo, A., & Maci, A. (2006). Heavy metals in marine sediments of Taranto Gulf (Ionian Sea, southern Italy). *Marine chemistry*, 99(1-4), 227-235.
- Bur, T., Probst, J.L., N'guessan, M., Probst, A., (2009). Distribution and origin of lead in stream sediments from small agricultural catchments draining Miocene molassic deposits (SW France). *Appl. Geochem.* 24, 1324–1338

- Cai, B., Ma, J., Yan, G., Dai, X., Li, M., Guo, S., (2016). Comparison of phytoremediation, bioaugmentation and natural attenuation for remediating saline soil contaminated by heavy crude oil. *Biochem. Eng. J.* 112, 170–177.
- Carberry, J. B., & Wik, J. (2001). Comparison of ex situ and in situ bioremediation of unsaturated soils contaminated by petroleum. *Journal of Environmental Science and Health, Part A*, 36(8), 1491-1503.
- Cardoso A, Boaventura G, Silva E, Brod J (2001) Metal distribution in sediments from the Ribiera bay, Rio de Janeiro Brazil. *J Braz Chem Soc* 12:767–774
- Cechinel, M. A. P., & de Souza, A. A. U. (2014). Study of lead (II) adsorption onto activated carbon originating from cow bone. *Journal of Cleaner Production*, 65, 342-349.
- Cetin, S., & Pehlivan, E. (2007). The use of fly ash as a low cost, environmentally friendly alternative to activated carbon for the removal of heavy metals from aqueous solutions. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 298(1-2), 83-87.
- Chaignon V (2001) Biodisponibilité du cuivre dans la rhizosphère de différentes plantes cultivées. Cas de sols viticoles contaminés par des fongicides. The`se: Ecole doctorale, Sciences de l'Environnement : Systeme Terre, Université d'Aix-Marseille, France
- Chapman PM, Wang F (2001) Assessing sediment contamination in estuaries. *Environ Toxicol Chem* 20: 3-22.
- Chen, S., Chao, L., Sun, L. N., & Sun, T. H. (2013). Plant-microorganism combined remediation for sediments contaminated with heavy metals. In *Advanced Materials Research* (Vol. 610, pp. 1223-1228). Trans Tech Publications.
- Chen, C., Liu, H., Chen, T., Chen, D., & Frost, R. L. (2015). An insight into the removal of Pb (II), Cu (II), Co (II), Cd (II), Zn (II), Ag (I), Hg (I), Cr (VI) by Na (I)-montmorillonite and Ca (II)-montmorillonite. *Applied Clay Science*, 118, 239-247.
- Chen, G., & White, P. A. (2004). The mutagenic hazards of aquatic sediments: a review. *Mutation Research/Reviews in Mutation Research*, 567(2-3), 151-225.

- Chen, Xiao, Hongbing Li, Xiaoyan Liu, Xinying Zhang, Xia Liang, Chiquan He, and Liya Cao. (2016). "Combined remediation of pyrene-contaminated soil with a coupled system of persulfate oxidation and phytoremediation with ryegrass." *Environmental Science and Pollution Research* 23, no. 20 :20672-20679.
- Chen, Y. G., He, Y., Ye, W. M., & Jia, L. Y. (2015). Competitive adsorption characteristics of Na (I)/Cr (III) and Cu (II)/Cr (III) on GMZ bentonite in their binary solution. *Journal of Industrial and Engineering Chemistry*, 26, 335-339.
- Chen, Y. G., He, Y., Ye, W. M., Lin, C. H., Zhang, X. F., & Ye, B. (2012). Removal of chromium (III) from aqueous solutions by adsorption on bentonite from Gaomiaozi, China. *Environmental earth sciences*, 67(5), 1261-1268.
- Chen, Y., Zhu, C., Sun, Y., Duan, H., Ye, W., & Wu, D. (2012). Adsorption of La (III) onto GMZ bentonite: effect of contact time, bentonite content, pH value and ionic strength. *Journal of Radioanalytical and Nuclear Chemistry*, 292(3), 1339-1347.
- Cheng, M., Zeng, G., Huang, D., Lai, C., Xu, P., Zhang, C., & Liu, Y. (2016a). Hydroxyl radicals based advanced oxidation processes (AOPs) for remediation of soils contaminated with organic compounds: a review. *Chemical Engineering Journal*, 284, 582-598.
- Chester, R., Thomas, A., Lim, F., Basaham, A. and Jacinto, A. (1988). The solid state speciation of copper in surface water particulate and oceanic sediment. *Mar. Chem.*, 24, 261–292.
- Chien, S.; Clayton, W. (1980) Application of Elovich equation to the kinetics of phosphate release and sorption in soils. *Soil Sci. Soc. Am. J.*, 44, 265–268.
- Cho Y-M, SmithenryDW, Ghosh U, Kennedy AJ, Millward RN, Bridges TS, Luthy RG (2007) Field methods for amending marine sediment with activated carbon and assessing treatment effectiveness. *Mar Environ Res* 64:541–555.
- Choi, Y., Cho, Y.M., Luthy, R.G., (2014). In situ sequestration of hydrophobic organic contaminants in sediments under stagnant contact with activated carbon. 1. Column studies. *Environ. Sci. Technol.* 48 (3), 1835–1842.

- Clean Water Team (CWT) (2004). Electrical conductivity/salinity Fact Sheet, FS3.1.3.0 (EC). in: The Clean Water Team Guidance Compendium for Watershed Monitoring and Assessment, Version 2.0. Division of Water Quality, California State Water Resources Control Board (SWRCB), Sacramento, CA.
- Coles, C. A., & Yong, R. N. (2002). Aspects of kaolinite characterization and retention of Pb and Cd. *Applied Clay Science*, 22(1-2), 39-45.
- Çoruh, S., & Geyikçi, F. (2012). Adsorption of copper (II) ions on montmorillonite and sepiolite clays: equilibrium and kinetic studies. *Desalination and Water Treatment*, 45(1-3), 351-360.
- Crini, G., & Badot, P. M. (Eds.). (2011). *Sorption processes and pollution: Conventional and non-conventional sorbents for pollutant removal from wastewaters*. Presses Univ. Franche-Comté
- Cruz-Guzmán, M., Celis, R., Hermosin, M. C., Koskinen, W. C., Nater, E. A., & Cornejo, J. (2006). Heavy metal adsorption by montmorillonites modified with natural organic cations. *Soil Science Society of America Journal*, 70(1), 215-221.
- Cukrov N, Francić-ković-Bilinski S, Hlača B, Barišić D (2011) A recent history of metal accumulation in the sediments of Rijeka harbor, Adriatic Sea, Croatia. *Mar Pollut Bull* 62:154–167
- Danková, Z., Bekényiová, A., Štyriaková, I., & Fedorová, E. (2015). Study of Cu (II) adsorption by siderite and kaolin. *Procedia Earth and Planetary Science*, 15, 821-826.
- Davidson, C. M., Ferreira, P. C., & Ure, A. M. (1999). Some sources of variability in application of the three-stage sequential extraction procedure recommended by BCR to industrially-contaminated soil. *Fresenius' journal of analytical chemistry*, 363(5-6), 446-451.
- Davidson CM, Duncan AL, Littlejohn D, Ure AM, Garden LM (1998) A critical Evaluation of the three-stage BCR sequential extraction procedure to assess the potential mobility and Toxicity of heavy metals in industrially-contaminated land. *Anal Chim Acta* 363: 45-55.
- Davidson, C.M. A.L. Duncan, D. Littlejohn, A.M. Ure and L.M. Garden, *Anal. Chim. Acta*, 363, 45-55 (1998).

- de Andrade Passos, E., Alves, J. C., dos Santos, I. S., Jose do Patrocínio, H. A., Garcia, C. A. B., & Costa, A. C. S. (2010). Assessment of trace metals contamination in estuarine sediments using a sequential extraction technique and principal component analysis. *Microchemical Journal*, 96(1), 50-57.
- de Pablo, L., Chávez, M. L., & Abatal, M. (2011). Adsorption of heavy metals in acid to alkaline environments by montmorillonite and Ca-montmorillonite. *Chemical engineering journal*, 171(3), 1276-1286.
- Duan, J., & Su, B. (2014). Removal characteristics of Cd (II) from acidic aqueous solution by modified steel-making slag. *Chemical Engineering Journal*, 246, 160-167.
- Eaton, A. D., Clesceri, L. S., Rice, E. W., Greenberg, A. E., & Franson, M. A. (2005). Standard methods for the examination of water and wastewater, 21st edn. American Public Health Association, American Waterworks Association, Water Environmental Federation.
- Eek, E., Cornelissen, G., Kibsgaard, A., & Breedveld, G. D. (2008). Diffusion of PAH and PCB from contaminated sediments with and without mineral capping; measurement and modelling. *Chemosphere*, 71(9), 1629-1638.
- Eek, E., Godøy, O., Aagaard, P., & Breedveld, G. D. (2007). Experimental determination of efficiency of capping materials during consolidation of metal-contaminated dredged material. *Chemosphere*, 69(5), 719-728.
- El-Temsah YS, Joner EJ (2013) Effects of nano-sized zero-valent iron (nZVI) on DDT degradation in soil and its toxicity to collembolan and ostracods. *Chemosphere* 92:131–137.
- EPA (U.S. Environmental Protection Agency) (1997). Toxicological Benchmarks for Screening Contaminants of Potential Concern for Effects on Sediment-Associated Biota, Report of the Sediment Criteria Subcommittee, Science Advisory Board. ES/ER/TM-95/R4.
- EPA (U.S. Environmental Protection Agency) (1997). Toxicological Benchmarks for Screening Contaminants of Potential Concern for Effects on Sediment-Associated Biota, Report of the Sediment Criteria Subcommittee, Science Advisory Board. ES/ER/TM-95/R4

- EPA, U.S., (1992). Framework for Ecological Risk Assessment. EPA/630/R-92/001. Risk Assessment Forum, U.S. Environmental Protection Agency, Washington, DC.
- EPA. US (1998) Assessment and Remediation of Contaminated Sediments (ARCS) Program: Guidance for in-situ Subaqueous Capping of Contaminated Sediments. Assessment and Remediation of Contaminated Sediments Program, Great Lakes National Program Office, Chicago
- Eren, E. (2008). Removal of copper ions by modified Unye clay, Turkey. *Journal of Hazardous Materials*, 159(2-3), 235-244.
- Eren, E., & Afsin, B. (2008). An investigation of Cu (II) adsorption by raw and acid-activated bentonite: A combined potentiometric, thermodynamic, XRD, IR, DTA study. *Journal of Hazardous Materials*, 151(2-3), 682-691.
- Esslemont G (2000) Heavy metals in seawater, marine sediments and corals from the Townsville section, Great Barrier Reef Marine Park, Queensland. *Marine Chemistry* 71: 215- 231.
- Fadaei, H., Watson, A., Place, A., Connolly, J., & Ghosh, U. (2015). Effect of PCB bioavailability changes in sediments on bioaccumulation in fish. *Environmental science & technology*, 49(20), 12405-12413.
- Fadaei, H., Watson, A., Place, A., Connolly, J., & Ghosh, U. (2015). Effect of PCB bioavailability changes in sediments on bioaccumulation in fish. *Environmental science & technology*, 49(20), 12405-12413.
- Faghihian, H., & Nejati-Yazdinejad, M. (2009). A comparative study of the sorption of Cd (II) and Pb (II) ions from aqueous solution by local bentonite and clinoptilolite. *Adsorption Science & Technology*, 27(1), 107-115.
- Fan W, Wang WX, Chen J (2002) Geochemistry of Cd, Cr, and Zn in highly contaminated sediments and its influences on assimilation by marine bivalves. *Environ Sci Technol* 36: 5164-5171.
- Fang, G. C., & Yang, H. C. (2011). Comparison of heavy metals in marine sediments from coast areas in East and Southeast Asian countries during the years 2000—2010. *Toxicology and industrial health*, 27(8), 754-759.
- Fangueiro, D., Bermond, A., Santos, E., Carapuç, H., & Duarte, A. (2005). Kinetic approach to heavy metal mobilization assessment in sediments: choose of

- kinetic equations and models to achieve maximum information. *Talanta*, 66(4), 844-857.
- Fashola, M. O., Ngole-Jeme, V. M., & Babalola, O. O. (2016). Heavy metal pollution from gold mines: environmental effects and bacterial strategies for resistance. *International journal of environmental research and public health*, 13(11), 1047
- Fatoki OS, Mathabata S (2001) An assessment of heavy metals pollution in the East London and Port Elizabeth harbours. *Water SA* 27: 233-240.
- Favas, P. J., Sarkar, S. K., & Rakshit, D. (2015). Geochemical fractionation of trace elements in stream sediments contaminated by mining activity. *CLEAN–Soil, Air, Water*, 43(3), 446-455.
- Feng, Y., Gong, J. L., Zeng, G. M., Niu, Q. Y., Zhang, H. Y., Niu, C. G., & Yan, M. (2010). Adsorption of Cd (II) and Zn (II) from aqueous solutions using magnetic hydroxyapatite nanoparticles as adsorbents. *Chemical Engineering Journal*, 162(2), 487-494.
- Fernández-Nava, Y., Ulmanu, M., Anger, I., Marañón, E., & Castrillón, L. (2011). Use of granular bentonite in the removal of mercury (II), cadmium (II) and lead (II) from aqueous solutions. *Water, Air, & Soil Pollution*, 215(1-4), 239-249.
- Filgueiras AV, Lavilla I, Bendicho C (2002) Chemical sequential extraction for metal Partitioning in environmental solid samples. *J of Environ Monit* 4: 823-857.
- Fjar, E., Holt, R. M., Raaen, A. M., Risnes, R., & Horsrud, P. (2008). *Petroleum related rock mechanics* (Vol. 53). Elsevier.
- Fofonoff, N. P. (1985). Physical properties of seawater: A new salinity scale and equation of state for seawater. *Journal of Geophysical Research: Oceans*, 90(C2), 3332-3342.
- Foo, K., & Hameed, B. (2010). Insights into the modeling of adsorption isotherm systems. *Chemical Engineering Journal*, 156(1), 2-10.
- Forstner U, Wittmann GTW (1981) Metal Pollution in the Aquatic Environment, Springer- Verlag, Berlin. Springer-Verlag, Heidelberg 486.

- Förstner, U., & Apitz, S. E. (2007). Sediment remediation: US focus on capping and monitored natural recovery. *Journal of Soils and Sediments*, 7(6), 351-358.
- Fotidis, I.A., Wang, H., Fiedel, N.R., Luo, G., Karakashev, D.B., Angelidaki, I., (2014). Bioaugmentation as a solution to increase methane production from an ammonia-rich substrate. *Environ. Sci. Technol.* 48 (13), 7669–7676.
- Francingues, K.E.G., Burton, G.A., Norman, R., Wolfe Jr., Danny, D.R., Donna, J.V., John, R., 2008. Evaluating the effectiveness of contaminated-sediment dredging. *Environ. Sci. Technol.* 42 (14), 5042e5047.
- Freije AM (2015) Heavy metal, trace element and petroleum hydrocarbon pollution in the Arabian Gulf: review. *J Assoc Arab Univ Basic Appl Sci* 17:90–100
- GESAMP(IMO/FAO/IJNESCO/WMO/IAEA/UN/IJNEP) (1982)
- Gaskell, T. F. (1973). *The gulf stream*. John Day Co..
- Gaucher, E. C., & Blanc, P. (2006). Cement/clay interactions—a review: experiments, natural analogues, and modeling. *Waste Management*, 26(7), 776-788.
- Gautam, R. K., Mudhoo, A., Lofrano, G., & Chattopadhyaya, M. C. (2014). Biomass-derived biosorbents for metal ions sequestration: Adsorbent modification and activation methods and adsorbent regeneration. *Journal of Environmental Chemical Engineering*, 2(1), 239-259.
- Gerhardt, K. E., Huang, X. D., Glick, B. R., & Greenberg, B. M. (2009). Phytoremediation and rhizoremediation of organic soil contaminants: potential and challenges. *Plant science*, 176(1), 20-30.
- Ghaedi, M., Ahmadi, F., & Soylak, M. (2007). Preconcentration and separation of nickel, copper and cobalt using solid phase extraction and their determination in some real samples. *Journal of Hazardous Materials*, 147(1-2), 226-231.
- Ghosh, U., Luthy, R. G., Cornelissen, G., Werner, D., & Menzie, C. A. (2011). In-situ Sorbent Amendments: A New Direction in Contaminated Sediment Management. *Environmental Science & Technology*, 45(4), 1163-1168.
- Gillespie, I. M., & Philp, J. C. (2013). Bioremediation, an environmental remediation technology for the bioeconomy. *Trends in biotechnology*, 31(6), 329-332.

- Gismera, M. J., Lacal, J., da Silva, P., García, R., Sevilla, M. T., & Procopio, J. R. (2004). Study of metal fractionation in river sediments. A comparison between kinetic and sequential extraction procedures. *Environmental Pollution*, 127(2), 175-182.
- Glatstein, D. A., & Francisca, F. M. (2015). Influence of pH and ionic strength on Cd, Cu and Pb removal from water by adsorption in Na-bentonite. *Applied Clay Science*, 118, 61-67.
- Goh, K. H., & Lim, T. T. (2004). Geochemistry of inorganic arsenic and selenium in a tropical soil: effect of reaction time, pH, and competitive anions on arsenic and selenium adsorption. *Chemosphere*, 55(6), 849-859.
- Gomes, H. I., Dias-Ferreira, C., & Ribeiro, A. B. (2013). Overview of in situ and ex situ remediation technologies for PCB-contaminated soils and sediments and obstacles for full-scale application. *Science of the Total Environment*, 445, 237-260.
- Gomez-Ariza JL, Giraldez I, Sanchez-Rodas D, Moralesm E (2000) Metal Sequential Extraction Procedure optimized for heavy metal polluted and iron- oxide rich sediments. *Anal Chim Acta* 414: 151-164.
- Gomez-Eyles, J. L., Yupanqui, C., Beckingham, B., Riedel, G., Gilmour, C., & Ghosh, U. (2013). Evaluation of biochars and activated carbons for in situ remediation of sediments impacted with organics, mercury, and methylmercury. *Environmental science & technology*, 47(23), 13721-13729.
- Gong, J. L., Wang, B., Zeng, G. M., Yang, C. P., Niu, C. G., Niu, Q. Y., & Liang, Y. (2009). Removal of cationic dyes from aqueous solution using magnetic multi-wall carbon nanotube nanocomposite as adsorbent. *Journal of hazardous materials*, 164(2-3), 1517-1522.
- Gong, X., Xu, X., Gong, Z., Li, X., Jia, C., Guo, M., & Li, H. (2015). Remediation of PAH-contaminated soil at a gas manufacturing plant by a combined two-phase partition system washing and microbial degradation process. *Environmental Science and Pollution Research*, 22 (16), 12001-12010.
- Grim, R. E. (1962). *Applied Clay Mineralogy* McGraw-Hill Book Company. New York, USA.

- Guevara-Riba A, Sahuquillo A, Rubio R, Rauret G (2004) Assessment of metal mobility in dredged harbour sediments from Barcelona, Spain. *Sci Total Environ* 321: 241-255.
- Guevara-Riba A, Sahuquillo A, Rubio R, Rauret G (2005) Effect of chloride on heavy metal mobility of harbour sediments. *Anal Bioanal Chem* 382: 353-359.
- Guiwei, Q., De Varennes, A., & Cunha-Queda, C. (2008). Remediation of a mine soil with insoluble polyacrylate polymers enhances soil quality and plant growth. *Soil Use and Management*, 24(4), 350-356.
- Guiwei, Q., de Varennes, A., Cunha-Queda, C., (2008). Remediation of a mine soil with insoluble polyacrylate polymers enhances soil quality and plant growth. *Soil Use Manag.* 24 (4), 350–356.
- Guo, X., Li, X., & Park, H. S. (2008). Ammonium and potassium removal for anaerobically digested wastewater using natural clinoptilolite followed by membrane pretreatment. *Journal of Hazardous Materials*, 151(1), 125-133.
- Gupta, S. S., & Bhattacharyya, K. G. (2005). Interaction of metal ions with clays: I. A case study with Pb (II). *Applied Clay Science*, 30(3-4), 199-208.
- Gupta, S. S., & Bhattacharyya, K. G. (2008). Immobilization of Pb (II), Cd (II) and Ni (II) ions on kaolinite and montmorillonite surfaces from aqueous medium. *Journal of environmental management*, 87(1), 46-58.
- Gupta, S. S., & Bhattacharyya, K. G. (2009). Treatment of water contaminated with Pb (II) and Cd (II) by adsorption on kaolinite, montmorillonite and their acid-activated forms.
- Gupta, S. S., & Bhattacharyya, K. G. (2012a). Natural and treated montmorillonites as scavengers of toxic metals from water. *Application of Adsorbents for Water Pollution Control*, 291.
- Gupta, S. S., & Bhattacharyya, K. G. (2012b). Using aqueous kaolinite suspension as a medium for removing phosphate from water. *Adsorption Science & Technology*, 30(6), 533-547.
- Gustavson, K. E.; Burton, G. A.; Francingues, N. R., Jr.; Reible, D. D.; Vorhees, D. J.; Wolfe, J. R. (2008). Evaluating the effectiveness of contaminated-sediment dredging. *Environ. Sci. Technol.* 42, 5042–5047.

- Fernandes, H. M. (1997). Heavy metal distribution in sediments and ecological risk assessment: the role of diagenetic processes in reducing metal toxicity in bottom sediments. *Environmental pollution*, 97(3), 317-325.
- Hakstege A (2007) Description of the available technology for treatment and disposal of dredged material. *Sediment Dredged Mater Treat* 2: 68–118.
- Han, H., Rafiq, M. K., Zhou, T., Xu, R., Mašek, O., & Li, X. (2019). A critical review of clay-based composites with enhanced adsorption performance for metal and organic pollutants. *Journal of hazardous materials*, 369, 780-796.
- Han, R., Zou, W., Zhang, Z., Shi, J., & Yang, J. (2006). Removal of copper (II) and lead (II) from aqueous solution by manganese oxide coated sand: I. Characterization and kinetic study. *Journal of Hazardous Materials*, 137(1), 384-395.
- Harikumar PS, Nasir UP, Rahman MPM (2009) Distribution of heavy metals in the core sediments of a tropical wetland system. *Int J Environ Sci Technol* 6:225–232
- Hatch, C. D., Wiese, J. S., Crane, C. C., Harris, K. J., Kloss, H. G., & Baltrusaitis, J. (2012). Water adsorption on clay minerals as a function of relative humidity: application of BET and Freundlich adsorption models. *Langmuir*, 28(3), 1790-1803.
- Hayes, M. A. B. (1974). CE Weaver and LD Pollard, *The Chemistry of Clay Minerals: Developments in Sedimentology*, Vol. 15, Elsevier Scientific Publishing Company, Amsterdam, 1973, viii+ 213 pp., price Dfl. 65.00 (ca. \$20.25).
- Hefne, J. A., Mekhemer, W. K., Al, N. M., Aldayel, O. A., & Alajyan, T. (2008). Kinetic and thermodynamic study of the adsorption of Pb (II) from aqueous solution to the natural and treated bentonite. *International Journal of Physical Sciences*, 3(11), 281-288.
- Hendricks, S. B. (1929). XVIII. Diffraction of X-Radiation from some Crystalline Aggregates. *Zeitschrift für Kristallographie-Crystalline Materials*, 71(1-6), 269-273.
- Hendricks, S. B., & Fry, W. H. (1930). The results of X-ray and microscopical examinations of soil colloids. *Soil Science*, 29(6), 457-480.

- Hizal, J., Apak, R., & Hoell, W. H. (2009). Modeling competitive adsorption of copper (II), lead (II), and cadmium (II) by kaolinite-based clay mineral/humic acid system. *Environmental progress & sustainable energy*, 28(4), 493-506.
- Ho, M. D., & Evans, G. J. (1997). Operational speciation of cadmium, copper, lead and zinc in the NIST standard reference materials 2710 and 2711 (Montana soil) by the BCR sequential extraction procedure and flame atomic absorption spectrometry. *Analytical Communications*, 34(11), 363-364.
- Hosseinpour, A.; Pashamokhtari, H. Impact of treated sewage sludge application on phosphorus release kinetics in some calcareous soils. *Environ. Geol.* 2008, 55, 1015–1021.
- Hu B, Li J, Zhao J, Yang J, Bai F, Dou Y (2013) Heavy metal in surface sediments of the Liaodong Bay, Bohai Sea: distribution, contamination, and sources. *Environ Monit Assess* 185:5071–5083
- Huang, D., Xu, Q., Cheng, J., Lu, X., Zhang, H., (2012). Electrokinetic remediation and its combined technologies for removal of organic pollutants from contaminated soils. *Int. J. Electrochem. Sci.* 7 (5), 4528–4544.
- Huifeng, Y., Wen, M., Weina, Z., & Zhiyong, W. (2011, February). Steel slag as multi-functional material for removal of heavy metal ions in wastewater. In *2011 International Conference on Computer Distributed Control and Intelligent Environmental Monitoring* (pp. 1287-1290). IEEE.
- Hull, J. H., J. M. Jersak and B. J. McDonald (1998). "Examination of a New Remedial Technology for Capping Contaminated Sediments: Large-Scale Laboratory Evaluation of Sediment Mixing and Cap Resistance to Erosive Forces." *Remediation Journal* 8(3): 37-58.
- Hull, J. H., Jersak, J. M., & Kasper, C. A. (1999). In Situ Capping Of Contaminated Sediments: Comparing The Relative Effectiveness Of Sand Versus Clay Mineral-Based Sediment Caps.
- Hyötyläinen T, Karels A, Oikari A (2002) Assessment of bioavailability and effects of chemicals due to remediation actions with caging mussels (*Anodonta anatina*) at a creosote-contaminated lake sediment site. *Water Res* 36:4497–4504.

- Idris AM, Eltayeb MAH, Potgieter-Vermaak SS, Grieken R, Potgieter JH (2007) Assessment of heavy metal pollution in Sudanese harbours along the Red Sea coast. *Microchemical. J* 87: 104-112.
- Ijagbemi, C. O., Baek, M. H., & Kim, D. S. (2009). Montmorillonite surface properties and sorption characteristics for heavy metal removal from aqueous solutions. *Journal of Hazardous materials*, 166(1), 538-546.
- Ismael, I. S. (2010). Synthesis and characterization of zeolite X obtained from kaolin for adsorption of Zn (II). *Chinese Journal of Geochemistry*, 29(2), 130-136.
- Iwegbue CMA, Egobueze FE K, Opuene K (2006) Preliminary assessment of heavy Metals Levels of soils of an oil field in the Niger Delta. *Int J Sci Technol* 3: 167-172.
- Jacobs, P. H., & Förstner, U. (1999). Concept of subaqueous capping of contaminated sediments with active barrier systems (ABS) using natural and modified zeolites. *Water Research*, 33(9), 2083-2087.
- Jain, C. K. (2004). Metal fractionation study on bed sediments of River Yamuna, India. *Water Research*, 38(3), 569-578.
- Janssen EML, Beckingham BA (2013) Biological responses to activated carbon amendments in sediment remediation. *Environ Sci Technol* 47:7595–7607.
- Jersak, J, Göransson, G, Ohlsson, Y, Larsson, L, Flyhammar, P & Lindh, P (2016). In-situ capping of contaminated sediments. In-situ capping of Sweden's fiberbank sediments: A unique challenge. SGI Publication 30-5E, Swedish Geotechnical Institute, SGI, Linköping.
- Jiang, M. Q., Jin, X. Y., Lu, X. Q., & Chen, Z. L. (2010). Adsorption of Pb (II), Cd (II), Ni (II) and Cu (II) onto natural kaolinite clay. *Desalination*, 252(1-3), 33-39.
- Jiang, M. Q., Wang, Q. P., Jin, X. Y., & Chen, Z. L. (2009). Removal of Pb (II) from aqueous solution using modified and unmodified kaolinite clay. *Journal of hazardous materials*, 170(1), 332-339.
- Jin, Y., Liu, W., Li, X. L., Shen, S. G., Liang, S. X., Liu, C., & Shan, L. (2016). Nano-hydroxyapatite immobilized lead and enhanced plant growth of ryegrass in a contaminated soil. *Ecological Engineering*, 95, 25-29.

- Joh, D., & Mbadcam, J. K. (2015). Adsorption of Zinc (II) ions from aqueous solution onto kaolinite and metakaolinite. *Der Pharmaceutical Chemical*, 7, 51-58.
- Jonker MT, Suijkerbuijk MP, Schmitt H, Sinnige TL (2009) Ecotoxicological effects of activated carbon addition to sediments. *Environ Sci Technol* 43:5959–5966.
- Josefsson S, Schaanning M, Samuelsson GS, Gunnarsson JS, Olofsson I, Eek E, Wiberg K (2012) Capping efficiency of various carbonaceous and mineral materials for in situ remediation of polychlorinated dibenzo-p-dioxin and dibenzofuran contaminated marine sediments: sediment-to-water fluxes and bioaccumulation in boxcosm tests. *Environ Sci Technol* 46:3343–3351.
- Juang, R. S., & Chen, M. L. (1997). Application of the Elovich equation to the kinetics of metal sorption with solvent-impregnated resins. *Industrial & Engineering Chemistry Research*, 36(3), 813-820.
- Kamil, J. and Shainberg, I. (1968) Hydrolysis of Na montmorillonite in sodium chloride solutions. *Soil Science*, 106, 193-199.
- Kandhal, P.S., and Parker, F. (1998). Aggregate tests related to asphalt concrete performance in pavements. National Cooperative Highway Research Program NCHRP Report 405.
- Kang, G., Park, K., Cho, J., Stevens, D.K., Chung, N., (2015). Remediation of polycyclic aromatic hydrocarbons in soil using hemoglobin-catalytic mechanism. *J. Environ. Eng.* 141 (10), 04015025.
- Kang, K., & Park, S. J. (2015). Application of limestone, zeolite, and crushed concrete as capping material for interrupting heavy metal release from marine sediments and reducing sediment oxygen demand. *Journal of the Korean Society of Agricultural Engineers*, 57(4), 31-38.
- Kang, K., Gu, B. W., & Park, S. J. (2016, April). Evaluation of sediment capping using zeolite, montmorillonite, and steel slag to immobilize heavy metals. In *OCEANS 2016-Shanghai*(pp. 1-5). IEEE.
- Kang, K., Lee, C. G., Choi, J. W., Kim, Y. K., & Park, S. J. (2016). Evaluation of the use of sea sand, crushed concrete, and bentonite to stabilize trace metals

- and to interrupt their release from contaminated marine sediments. *Water, Air, & Soil Pollution*, 227(9), 308.
- Kang, K., Lee, C. G., Choi, J. W., Kim, Y. K., & Park, S. J. (2016). Evaluation of the use of sea sand, crushed concrete, and bentonite to stabilize trace metals and to interrupt their release from contaminated marine sediments. *Water, Air, & Soil Pollution*, 227(9), 308.
- Karamanis, D., & Assimakopoulos, P. A. (2007). Efficiency of aluminum-pillared montmorillonite on the removal of cesium and copper from aqueous solutions. *Water research*, 41(9), 1897-1906.
- Karapinar, N., & Donat, R. (2009). Adsorption behaviour of Cu^{2+} and Cd^{2+} onto natural bentonite. *Desalination*, 249(1), 123-129.
- Khan, S., Afzal, M., Iqbal, S., Khan, Q.M., (2013). Plant-bacteria partnerships for the remediation of hydrocarbon contaminated soils. *Chemosphere* 90 (4), 1317–1332.
- Knox A, Kaplan D, Paller, M (2006) Phosphate sources and their suitability for remediation of contaminated soils. *Sci Total Environ* 357: 271–279.
- Knox, A. S., Paller, M. H., & Roberts, J. (2012). Active capping technology—new approaches for in situ remediation of contaminated sediments. *Remediation Journal*, 22(2), 93-117.
- Kónya, J., & Nagy, N. (2011). Sorption of dissolved mercury (II) species on calcium-montmorillonite: an unusual pH dependence of sorption process. *Journal of Radioanalytical and Nuclear Chemistry*, 288(2), 447-454.
- Kress, N., Herut, B., & Galil, B. S. (2004). Sewage sludge impact on sediment quality and benthic assemblages off the Mediterranean coast of Israel—a long-term study. *Marine Environmental Research*, 57(3), 213-233.
- Kubilay, Ş., Gürkan, R., Savran, A., & Şahan, T. (2007). Removal of Cu (II), Zn (II) and Co (II) ions from aqueous solutions by adsorption onto natural bentonite. *Adsorption*, 13(1), 41-51.
- KubilayMohellebi, F., & Lakel, F. (2016). Adsorption of Zn^{2+} on Algerian untreated bentonite clay. *Desalination and Water Treatment*, 57(13), 6051-6062.
- Kueper, B.H., Stroo, H.F., Vogel, C.M., Ward, C.H., 2014. Chlorinated Solvent Source Zone Remediation. Springer.

- Kul, A. R., & Caliskan, N. (2009). Equilibrium and kinetic studies of the adsorption of Zn (II) ions onto natural and activated kaolinites. *Adsorption Science & Technology*, 27(1), 85-105.
- Kul, A. R., & Koyuncu, H. (2010). Adsorption of Pb (II) ions from aqueous solution by native and activated bentonite: kinetic, equilibrium and thermodynamic study. *Journal of Hazardous Materials*, 179(1-3), 332-339.
- Kumar, A. S. K., Kalidhasan, S., Rajesh, V., & Rajesh, N. (2012). A meticulous study on the adsorption of mercury as tetrachloromercurate (II) anion with trioctylamine modified sodium montmorillonite and its application to a coal fly ash sample. *Industrial & Engineering Chemistry Research*, 51(35), 11312-11327.
- Kuppusamy, S., Palanisami, T., Megharaj, M., Venkateswarlu, K., & Naidu, R. (2016). In-situ remediation approaches for the management of contaminated sites: a comprehensive overview. In *Reviews of Environmental Contamination and Toxicology Volume 236* (pp. 1-115). Springer, Cham.
- Kupryianchyk, D., Rakowska, M. I., Reible, D., Harmsen, J., Cornelissen, G., van Veggel, M., ... & Koelmans, A. A. (2015). Positioning activated carbon amendment technologies in a novel framework for sediment management. *Integrated environmental assessment and management*, 11(2), 221-234.
- Kutuniva, J., Mäkinen, J., Kauppila, T., Karppinen, A., Hellsten, S., Luukkonen, T., & Lassi, U. (2019). Geopolymers as active capping materials for in situ remediation of metal (loid)-contaminated lake sediments. *Journal of Environmental Chemical Engineering*, 7(1), 102852.
- Lampert, D. J., Sarchet, W. V., & Reible, D. D. (2011). Assessing the effectiveness of thin-layer sand caps for contaminated sediment management through passive sampling. *Environmental science & technology*, 45(19), 8437-8443.
- Lampert, D. J., Stegemann, J. A., & Reible, D. D. (2009). Predicting contaminant fate and transport in sediment caps: mathematical modelling approaches. *Applied Geochemistry*, 24(7), 1347-1353.

- Larsson, P. (1985). Contaminated sediments of lakes and oceans act as sources of chlorinated hydrocarbons for release to water and atmosphere. *Nature*, 317(6035), 347.
- Lasheen, M. R., El-Sherif, I. Y., Sabry, D. Y., El-Wakeel, S. T., & El-Shahat, M. F. (2016). Adsorption of heavy metals from aqueous solution by magnetite nanoparticles and magnetite-kaolinite nanocomposite: equilibrium, isotherm and kinetic study. *Desalination and Water Treatment*, 57(37), 17421-17429.
- Lee J, Fox PJ (2009) Investigation of consolidation-induced solute transport. II: experimental and numerical results. *J Geotech Geoenviron Eng* 135:1239–1253.
- Lee, H., Lee, Y., Kim, J., Kim, C., (2014). Field application of modified in situ soil flushing in combination with air sparging at a military site polluted by diesel and gasoline in Korea. *Int. J. Environ. Res. Public Health* 11 (9), 8806–8824.
- Leleyter, L., & Baraud, F. (2005). Évaluation de la mobilité des métaux dans les sédiments fluviaux du bassin de la Vire (Normandie, France) par extractions simples ou séquentielles. *Comptes Rendus Geoscience*, 337(6), 571-579.
- Leleyter, L., & Probst, J. L. (1999). A new sequential extraction procedure for the speciation of particulate trace elements in river sediments. *International Journal of Environmental Analytical Chemistry*, 73(2), 109-128.
- Leschber, R., Davis, R. D., & L'Hermite, P. (1985). Chemical methods for assessing bio-available metals in sludges and soils.
- Li, J., Li, Y., & Meng, Q. (2010). Removal of nitrate by zero-valent iron and pillared bentonite. *Journal of hazardous materials*, 174(1-3), 188-193.
- Liang Y, Wong MH (2003) Spatial and temporal organic and heavy metal pollution at Mai Po Marshes Nature Reserve, Hong Kong. *Chemosphere* 52:1647-1658.
- Lim, S. F., & Lee, A. Y. W. (2015). Kinetic study on removal of heavy metal ions from aqueous solution by using soil. *Environmental Science and Pollution Research*, 22(13), 10144-10158.

- Lin, J. G., & Chen, S. Y. (1998). Mobilization kinetics of heavy metals from contaminated river sediment of Northern Taiwan by complexing agents. *Toxicological & Environmental Chemistry*, 67(3-4), 511-529.
- Liu, Q., Yang, B., Zhang, L., & Huang, R. (2015). Adsorptive removal of Cr (VI) from aqueous solutions by cross-linked chitosan/bentonite composite. *Korean Journal of Chemical Engineering*, 32(7), 1314-1322.
- Luo W, Lu Y, Wang T, Hu W, Jiao W, Naile JE, Khim JS, Giesy JP (2010) Ecological risk assessment of arsenic and elements in sediments of coastal areas of Northern Bohai and Yellow Seas, China. *Ambio* 39:367–375
- Luo, Y. M., & Christie, P. (1998). Choice of extraction technique for soil reducible trace metals determines the subsequent oxidisable metal fraction in sequential extraction schemes. *International journal of environmental analytical chemistry*, 72(1), 59-75.
- Ma, C., & Eggleton, R. A. (1999). Cation exchange capacity of kaolinite. *Clays and Clay minerals*, 47(2), 174-180.
- Ma, L., Chen, Q., Zhu, J., Xi, Y., He, H., Zhu, R., ... & Ayoko, G. A. (2016). Adsorption of phenol and Cu (II) onto cationic and zwitterionic surfactant modified montmorillonite in single and binary systems. *Chemical Engineering Journal*, 283, 880-888.
- Ma, L., Zhu, J., Xi, Y., Zhu, R., He, H., Liang, X., & Ayoko, G. A. (2015). Simultaneous adsorption of Cd (II) and phosphate on Al 13 pillared montmorillonite. *RSC Advances*, 5(94), 77227-77234.
- Ma, X., Anand, D., Zhang, X., Tsige, M., & Talapatra, S. (2010). Carbon nanotube-textured sand for controlling bioavailability of contaminated sediments. *Nano Research*, 3(6), 412-422.
- MacDonald DD, Ingersoll CG, Berger TA (2000) Development and evaluation of consensus-based sediment quality guidelines for freshwater ecosystems. *Arch Environ Contam Toxicol* 39:20–31
- Magar, V. S., D. B. Chadwick, T. S. Bridges, P. C. Fuchsman, J. M. Conder, T. J. Dekker, J. A. Steevens, K. E. Gustavson and M. A. Mills (2009). Monitored natural recovery at contaminated sediment sites, DTIC Document.

- Malkoc, E., & Nuhoglu, Y. (2007). Determination of kinetic and equilibrium parameters of the batch adsorption of Cr (VI) onto waste acorn of *Quercus ithaburensis*. *Chemical Engineering and Processing-Process Intensification*, 46(10), 1020-1029.
- Manap, N. and N. Voulvoulis (2016). "Data analysis for environmental impact of dredging." *Journal of Cleaner Production* 137: 394-404.
- Mao, X., Jiang, R., Xiao, W., Yu, J., (2015). Use of surfactants for the remediation of contaminated soils: *a review*. *J. Hazard. Mater.* 285, 419–435.
- Marcussen, H., Holm, P. E., Strobel, B. W., & Hansen, H. C. B. (2009). Nickel sorption to goethite and montmorillonite in presence of citrate. *Environmental science & technology*, 43(4), 1122-1127.
- Martins M, Costa PM, Raimundo J, Vale C, Ferreira AM, Costa MH (2012) Impact of remobilized contaminants in *Mytilus edulis* during dredging operations in a harbour area: bioaccumulation and biomarker responses. *Ecotoxicol Environ Saf* 85:96–103.
- Mashiatullah A, Chaudhary MZ, Ahmad N, Javed T, Ghaffar A (2013) Metal pollution and ecological risk assessment in marine sediments of Karachi Coast, Pakistan. *Environ Monit Assess* 185:1555–1565
- Matłok, M., Petrus, R., & Warchoł, J. K. (2015). Equilibrium study of heavy metals adsorption on kaolin. *Industrial & Engineering Chemistry Research*, 54(27), 6975-6984.
- McDonough K.M, Murphy P, Olsta J, Zhu Y, Reible D, Lowry GV (2007) Development and placement of a sorbent-amended thin layer sediment cap in the Anacostia River. *Soil Sediment Contam Int J* 16: 313–322.
- Meki C, Olusegun A, Yerokun (2012). The distribution of Zinc fractions in surface samples of selected agricultural soils of Zambia. *International Journal of Soil Science*, 7: 51-60.
- Merabet, S.; Boukhalfa, C.; Chellat, S.; Boultif, A. Characterization of chromium (III) removal from water by river bed sediments: Kinetic and Equilibrium studies. *J. Mater. Environ. Sci.* 2016, 7, 1624–1632.
- Michael R. Palermo (1997), "In-Situ Capping of Contaminated Sediment Overview and Case Studies", Proceedings Cincinnati, OH May 13-14, 1997, National Conference on Management and Treatment of Contaminated

Sediments, United States Environmental Protection Agency, Office of Research and Development Washington, DC.

- Millero, F. J., Feistel, R., Wright, D. G., & McDougall, T. J. (2008). The composition of Standard Seawater and the definition of the Reference-Composition Salinity Scale. *Deep Sea Research Part I: Oceanographic Research Papers*, 55(1), 50-72.
- Mining, S., & Kennedy, B. A. (1990). Society for Mining, Metallurgy and Exploration. *Inc., Littleton, Colorado*.
- Miranda-Trevino, J. C., & Coles, C. A. (2003). Kaolinite properties, structure and influence of metal retention on pH. *Applied Clay Science*, 23(1-4), 133-139.
- Mitchell, J. K., & Soga, K. (2005). *Fundamentals of soil behavior* (Vol. 3). Hoboken, NJ: John Wiley & Sons.
- Mohan, R., J. P. Doody, C. Patmont, R. Gardner and A. Shellenberger (2016). "Review of environmental dredging in north america: current practice and lessons learned." *Journal of Dredging* 15(2): 29.
- Mohapatra, D., Mishra, D., Chaudhury, G. R., & Das, R. P. (2007). Arsenic (V) adsorption mechanism using kaolinite, montmorillonite and illite from aqueous medium. *Journal of Environmental Science and Health, Part A*, 42(4), 463-469.
- Murphy P, Marquette A, Reible D, Lowry GV (2006) Predicting the performance of activated carbon-, coke-, and soil-amended thin layer sediment caps. *J Environ Eng* 132:787–794.
- Murphy T., Moller A., and Brouwer H. (1995b). In situ treatment of Hamilton Harbor sediment, *Journal of Aquatic Ecosystem Health*, Vol 4, pp. 195-203.
- Murray, H. H. (1999). Applied clay mineralogy today and tomorrow. *Clay minerals*, 34(1), 39-49. [64] Carr, D. D., Alsobrook, A. F., & Austin, G. (1994). *Industrial Minerals and Rocks*. Society for Mining, Metallurgy, and Exploration. *Inc., Littleton, Colorado*.
- Najib, N. W., Mohammed, S. A., Ismail, S. H., & Ahmad, W. A. (2012). Assessment of heavy metal in soil due to human activities in Kangar, Perlis, Malaysia. *Int J Civil Environ Eng [Internet]*, 12(6), 28-33.

- Naser HA (2013) Assessment and management of heavy metal pollution in the marine environment of the Arabian Gulf: a review. *Mar Pollut Bull* 72:6–13
- Näslund J, Samuelsson GS, Gunnarsson JS, Nascimento FJ, Nilsson H, Cornelissen G, Schaanning M (2012) Ecosystem effects of materials proposed for thin-layer capping of contaminated sediments. *Mar Ecol Prog Ser* 449:27–39.
- National Research Council prepared by Committee on Contaminated Marine Sediments, National Academy Press, Washington, D.C.
- Nayar S, Goh B, Chou L (2004) Environmental impact of heavy metals from dredged and resuspended sediments on phytoplankton and bacteria assessed in situ mesocosms. *Ecotoxicol Environ Saf* 59: 349–369.
- Ndazi B, Tesha JV, Bisanda TN (2007) Some opportunities and challenges of producing bio-composites from non-wood residues. *J Mater Sci* 41:6984–6990
- Nevins, M. J., & Weintritt, D. J. (1967). Determination of cation exchange capacity by methylene blue adsorption. *American Ceramic Society Bulletin*, 46(6), 587-+.
- New York State Department of Environmental Conservation Division of Fish, Wildlife and Marine Resources. (1993). Technical Guidance for Screening Contaminated Sediments. Pekey
- N'guessan, Y. M., Probst, J. L., Bur, T., & Probst, A. (2009). Trace elements in stream bed sediments from agricultural catchments (Gascogne region, SW France): where do they come from?. *Science of the total environment*, 407(8), 2939-2952.
- Nobi EP, Dilipan E, Thangaradjou T, Sivakumar K, Kannan L (2010) Geochemical and geo-statistical assessment of heavy metal concentration in the sediments of different coastal ecosystems of Andaman Islands, India. *Estuar Coast Shelf Sci* 87:253–264
- Novaković, T., Rožić, L., Petrović, S., & Rosić, A. (2008). Synthesis and characterization of acid-activated Serbian smectite clays obtained by statistically designed experiments. *Chemical Engineering Journal*, 137(2), 436-442.

- NRC (National Research Council). (1997). Contaminated Sediments in Ports and Waterways: Cleanup Strategies and Technologies. National Academies Press, Washington, DC, USA.
- Nussmann, D. G. (1965). *Trace elements in the sediments of Lake Superior* (Doctoral dissertation).
- O'Connell, D. W., Birkinshaw, C., & O'Dwyer, T. F. (2008). Heavy metal adsorbents prepared from the modification of cellulose: A review. *Bioresource technology*, 99(15), 6709-6724.
- Okoye, I. P., & Obi, C. (2012). Thermodynamic and kinetic evaluations of some heavy metal ions on aluminum-pillared and unpillared bentonite clays. *International Archive of Applied Sciences and Technology*, 3(2), 58-67.
- Olu-Owolabi, B. I., Alabi, A. H., Unuabonah, E. I., Diagbaya, P. N., Böhm, L., & Düring, R. A. (2016). Calcined biomass-modified bentonite clay for removal of aqueous metal ions. *Journal of environmental chemical engineering*, 4(1), 1376-1382.
- Omar, W., & Al-Itawi, H. (2007). Removal of Pb²⁺ Ions from Aqueous Solutions by adsorption on kaolinite clay. *American Journal of Applied Sciences*, 4(7), 502-507.
- Oubagaranadin, J. U. K., Murthy, Z. V., & Mallapur, V. P. (2010). Removal of Cu (II) and Zn (II) from industrial wastewater by acid-activated montmorillonite-illite type of clay. *Comptes Rendus Chimie*, 13(11), 1359-1363.
- Özkundakci D, Duggan IC, Hamilton DP (2011) Does sediment capping have post-application effects on zooplankton and phytoplankton? *Hydrobiologia* 661:55–64.
- Palermo, M. (2015). Construction and Navigation Tolerances for Cap Design. In Remediation of Contaminated Sediments - 2015. Proceedings of the Eighth International Conference on Remediation of Contaminated Sediments. Battelle, primary sponsor. New Orleans, LA, January 12-15, 2015.

- Palermo, M. and D. Reible. (2007). The Evolution of Cap Design. Proceedings, World Dredging Congress WODCON XVIII, Orlando, FL, May 27-June1, 2007.
- Palermo, M. R., Hinchee, R., Porta, A., & Pellei, M. (2001). A state of the art overview of contaminated sediment remediation in the United States. In *Proceedings of the International Conference on Remediation of Contaminated Sediments* (pp. 10-12).
- Paller MH, Knox AS (2010) Amendments for the in situ remediation of contaminated sediments: Evaluation of potential environmental impacts. *Sci Total Environ* 408:4894–4900.
- Pan K, Wang W-X (2012) Trace metal contamination in estuarine and coastal environments in China. *Sci Total Environ* 421(422):3–16
- Pan, M., Lin, X., Xie, J., & Huang, X. (2017). Kinetic, equilibrium and thermodynamic studies for phosphate adsorption on aluminum hydroxide modified palygorskite nano-composites. *RSC Adv.*, 7(8), 4492–4500.
- Panda, A. K., Mishra, B. G., Mishra, D. K., & Singh, R. K. (2010). Effect of sulphuric acid treatment on the physico-chemical characteristics of kaolin clay. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 363(1–3), 98–104.
- Pardo, R., Barrado, E., Castrillejo, Y., Velasco, M.A. and M. Vega (1993). Study of the contents and speciation of heavy metals in River sediments by factor analysis. *Analytical Letters*, 26: 1719-1739
- Park, J.H., Choppala, G.K., Bolan, N.S., Chung, J.W., Chuasavathi, T., (2011). Biochar reduces the bioavailability and phytotoxicity of heavy metals. *Plant Soil* 348 (1–2), 439–451.
- Park, S. J., Kang, K., Lee, C. G., & Choi, J. W. (2019). Remediation of metal-contaminated marine sediments using active capping with limestone, steel slag, and activated carbon: a laboratory experiment. *Environmental technology*, 40(26), 3479-3491.
- Parker, S. P. (1988). *McGraw-Hill encyclopedia of the geological sciences*. McGraw-Hill Press, 1988, pp. 32–33, 69–72, 400–401

- Parrett, K. and H. Blishke (2005). "23 Acre Multilayer Sediment Cap in Dynamic Riverine Environment Using organoclay an adsorptive Capping Material." SETAC Presentation.
- Pauling, L. (1930). The structure of the chlorites. *Proceedings of the National Academy of Sciences of the United States of America*, 16(9), 578.
- Pazi I (2011) Assessment of heavy metal contamination in Candarli Gulf sediment, Eastern Aegean Sea. *Environ Monit Assess* 174:199–208
- Peddicord, R.K, C.R. Lee, and R.M Engler. (1998). Use of sediment quality Guideline (SQG) in dredged material management. Dredge Research Technical Note EEDP-04-29. Long-Term Effects of Dredging Operations Program. U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS
- Pei, Z., Shan, X. Q., Kong, J., Wen, B., & Owens, G. (2009). Coadsorption of ciprofloxacin and Cu (II) on montmorillonite and kaolinite as affected by solution pH. *Environmental science & technology*, 44(3), 915-920.
- Pempkowiak J, Sikora A, Biernacka E (1999) Speciation of heavy metals in marine sediments vs their bioaccumulation by mussels. *Chemosphere* 39: 313-321.
- Peng, J.F., Song, Y.H., Yuan, P., Cui, X.Y., Qiu, G.L., 2009. The remediation of heavy metals contaminated sediment. *J. Hazard. Mater.* 161 (2–3), 633–640.
- Peng, L., Deng, D., Ye, F., 2015. Efficient oxidation of high levels of soil-sorbed phenanthrene by microwave-activated persulfate: implication for in situ subsurface remediation engineering. *J. Soils Sed.* 16 (1), 28–37.
- Perelo, L. W. (2010). "Review: in situ and bioremediation of organic pollutants in aquatic sediments." *Journal of Hazardous Materials* 177(1): 81-89.
- Pérez-Marín, A. B., V. Meseguer Zapata, J. F. Ortuno, M. Aguilar, J. Sáez, and M. Lloréns. "Removal of cadmium from aqueous solutions by adsorption onto orange waste." *Journal of hazardous materials* 139, no. 1 (2007): 122-131.
- Petit, M. D., & Rucandio, M. I. (1999). Sequential extractions for determination of cadmium distribution in coal fly ash, soil and sediment samples. *Analytica Chimica Acta*, 401(1-2), 283-291.

- Pizzaro I, Gomez M, Camara C, Palacios MA (2003) Arsenic speciation in Environmental and biological samples –Extraction and stability studies. *Anal Chim Acta* 495: 85-98.
- Ponnamperuma, F. N. (1972). The chemistry of submerged soils. In *Advances in agronomy* (Vol. 24, pp. 29-96). Academic Press.
- Preetha, B., & Viruthagiri, T. (2007). Batch and continuous biosorption of chromium (VI) by *Rhizopus arrhizus*. *Separation and Purification Technology*, 57(1), 126-133.
- Ra K, Kim J-K, Hong SH, Yim UH, Shim WJ, Lee S-Y, Kim Y-O, Lim J, Kim E-S, Kim K-T (2014) Assessment of pollution and ecological risk of heavy metals in the surface sediments of Ulsan Bay, Korea. *Ocean Sci J* 49:279–289
- Rakowska, M., D. Kupryianchyk, J. Harmsen, T. Grotenhuis and A. Koelmans (2012). "In situ remediation of contaminated sediments using carbonaceous materials." *Environmental Toxicology and Chemistry* 31(4): 693-704.
- Randall PM, Yates BJ, Lal V, Darlington R, Fimmen R (2013) In-situ subaqueous capping of mercury-contaminated sediments in a freshwater aquatic system, Part II-evaluation of sorption materials. *Environ Res* 125:41–51.
- Rath, P., Panda, U.C., Bhatta, D. and K.C. Sahu (2009). Use of sequential leaching, mineralogy, morphology and multivariate statistical technique for quantifying metal pollution in highly polluted aquatic sediments--a case study: Brahmani and Nandira Rivers, India. *Journal of Hazardous Material*, 16: 632-644.
- Rauret G (1998) Extraction procedures for the determination of heavy metals in contaminated soil and sediment. *Talanta* 46: 449-455.
- Rauret G, Lopez-Sanchez JF (2001) New sediment and soil CRMs for extractable Trace metal content. *Int J Environ Anal Chem* 79: 81-95.
- Reible D, Hayes D, Lue-Hing C, Patterson J, Bhowmik N, Johnson M, Teal J (2003) Comparison of the long-term risks of removal and in situ management of contaminated sediments in the Fox River. *Soil Sediment Contam* 12:325–344.

- Reible, D. (2008). Modeling for the Design of Active Layers for Contaminated Sediment Caps. *Report prepared for CETCO Remediation Technologies. Technical Reference TR-821*. May 2008.
- Reible, D. and D. Lampert. (2014). Capping for Remediation of Contaminated Sediments, Chapter 12. In: *Processes, Assessment and Remediation of Contaminated Sediments* (D. Reible, editor). *Published by Springer*. 462 p
- Reible, D. D. (Ed.). (2014). *Processes, assessment and remediation of contaminated sediments* (pp. 365-391). *New York: Springer*.
- Reichenbach, H. G. V. (1980). BKG Theng: Formation and properties of clay-polymer complexes.(Developments in soil science, 9) XII, 362 Seiten, Preis 58, Elsevier Scientific Publishing Company, Amsterdam, Oxford, New York, 1979. *Zeitschrift für Pflanzenernährung und Bodenkunde*, 143(3), 359-359.
- Relić, D., Đorđević, D., Sakan, S., Anđelković, I., Pantelić, A., Stanković, R., & Popović, A. (2013). Conventional, microwave, and ultrasound sequential extractions for the fractionation of metals in sediments within the Petrochemical Industry, Serbia. *Environmental monitoring and assessment*, 185(9), 7627-7645.
- Riba I, Garc í-Luque E, Blasco J, Del Valls TA (2003) Bioavailability of heavy metals bound to estuarine sediments as a function of pH and salinity values. *Chemical Speciation and Bioavailability* 15: 101-114.
- Riba I, Garc í-Luque E, Maz-Courrau A de, Canales G M LM, DelValls TA (2010) Influence of Salinity in the Bioavailability of Zn in Sediments of the Gulf of Cádiz(Spain). *Water Air and Soil Pollution* 212: 329-336.
- Roberts DA (2012) Causes and ecological effects of resuspended contaminated sediments (RCS) in marine environments. *Environ Int*. 40: 230–243.
- Rosen G, Leather J, Kan J, Arias-Thode YM (2011) Ecotoxicological response of marine organisms to inorganic and organic sediment amendments in laboratory exposures. *Ecotoxicol Environ Saf* 74: 1921–1930.
- Ross, C. S., & Hendricks, S. B. (1945). *Minerals of the montmorillonite group, their origin and relation to soils and clays* (No. 205-B).

- Ross, C.S. (1999) The mineralogy of clays, in: Transactions of the 1st International Congress of Soil Science, Washington, D.C., 4, pp. 555–561.
- Rubinos, D. A.; Iglesias, L.; Díaz-Fierros, F.; Barral, M. T. Interacting effect of pH, phosphate and time on the release of arsenic from polluted river sediments (Anllóns River, Spain). *Aquat. Geochem.* 2011, 17, 281–306.
- Ruilian YU, Xing Y, Yuanhui Z, Gongren HU, Xianglin TU (2008) Heavy metal pollution in intertidal sediments from Quanzhou Bay, China. *J Environ Sci* 20:664–669
- Saleem, M., Iqbal, J., Akhter, G., & Shah, M. H. (2018). Fractionation, bioavailability, contamination and environmental risk of heavy metals in the sediments from a freshwater reservoir, Pakistan. *Journal of Geochemical Exploration*, 184, 199-208.
- Samaksaman, U., Peng, T.H., Kuo, J.H., Lu, C.H., Wey, M.Y., (2016). Thermal treatment of soil co-contaminated with lube oil and heavy metals in a low-temperature two-stage fluidized bed incinerator. *Appl. Therm. Eng.* 93, 131–138.
- Samanidou, V. and K. Fytianos (1987). Partitioning of heavy metals into selective chemical fractions in sediments from rivers in northern Greece. *The Science of the Total Environment*, **67**: 279-285
- Samuelsson, G.S., Hedman, J.E., Elmquist Kruså M., Gunnarsson, J.S., Cornelissen, G., (2015). Capping in situ with activated carbon in Trondheim harbor (Norway) reduces bioaccumulation of PCBs and PAHs in marine sediment fauna. *Mar. Environ. Res.* 109, 103–112.
- Sandu, C., Popescu, M., Rosales, E., Bocos, E., Pazos, M., Lazar, G., et al., (2016). Electrokinetic-Fenton technology for the remediation of hydrocarbons historically polluted sites. *Chemosphere* 156, 347–356.
- Sany SBT, Salleh A, Sulaiman AH, Sasekumar A, Rezayi M, Tehrani GM (2013) Heavy metal contamination in water and sediment of the Port Klang coastal area, Selangor, Malaysia. *Environ Earth Sci* 69:2013–2025
- Sany, B. T., Sulaiman, A. H., Monazami, G. H., & Salleh, A. (2011). Assessment of sediment quality according to heavy metal status in the West Port of Malaysia. *World Academy of Science, Engineering and Technology*, 74, 639-643.

- Sari, A., Tuzen, M., Citak, D., & Soylak, M. (2007). Equilibrium, kinetic and thermodynamic studies of adsorption of Pb (II) from aqueous solution onto Turkish kaolinite clay. *Journal of hazardous materials*, 149(2), 283-291.
- Sebogodi, K. M., & Babalola, O. O. (2011). Identification of soil bacteria from mining environments in Rustenburg, South Africa. *Life Sci. J*, 8, 25-32.
- Sen, T. K., & Gomez, D. (2011). Adsorption of zinc (Zn^{2+}) from aqueous solution on natural bentonite. *Desalination*, 267(2-3), 286-294.
- Sharifuzzaman, S. M., Rahman, H., Ashekuzzaman, S. M., Islam, M. M., Chowdhury, S. R., & Hossain, M. S. (2016). Heavy metals accumulation in coastal sediments. In *Environmental remediation technologies for metal-contaminated soils* (pp. 21-42). Springer, Tokyo.
- Sheha, R. R., & El-Zahhar, A. A. (2008). Synthesis of some ferromagnetic composite resins and their metal removal characteristics in aqueous solutions. *Journal of Hazardous Materials*, 150(3), 795-803.
- Shi, L. N., Lin, Y. M., Zhang, X., & Chen, Z. L. (2011). Synthesis, characterization and kinetics of bentonite supported nZVI for the removal of Cr (VI) from aqueous solution. *Chemical Engineering Journal*, 171(2), 612-617.
- Silva, I. A., Costa, J. M. R., Menezes, R. R., Ferreira, H. S., Neves, G. D. A., & Ferreira, H. C. (2013). Studies of new occurrences of bentonite clays in the State of Paraíba for use in water based drilling fluids. *Rem: Revista Escola de Minas*, 66(4), 485-491.
- Singh S, Ma L, Harris W (2001) Heavy metal interactions with phosphatic clay: sorption and desorption behavior. *J Environ Qual* 30:1961–1968
- Song, B., Yi, Y.M., Park, S., Munster, C., Kim, G., Zeng, G., Gong, J., Zhang, P., Deng, J., Deng, C., et al., 2017. Effect of multiwalled carbon nanotubes on phytotoxicity of sediments contaminated by phenanthrene and cadmium. *Chemosphere* 172, 449–458.
- Sposito, G. (2008). *The chemistry of soils*. Oxford university press.
- Srinivasan, R. (2011). Advances in application of natural clay and its composites in removal of biological, organic, and inorganic contaminants from drinking water. *Advances in Materials Science and Engineering*, 2011.

- Standard, B. BS1377: PART 2, 1990. *Methods of tests of soils for civil engineering purposes–Classification Tests*.
- Stankovic, M. S. (2011). Total phenolic content, flavonoid concentration and antioxidant activity of *Marrubium peregrinum* L. extracts. *Kragujevac J Sci*, 33(2011), 63-72.
- Stephens SR, Alloway BJ, Parker A, Carter JE, Hodson ME (2001) Changes in the leachability of metals from dredged canal sediments during drying and oxidation. *Environ Pollut* 114: 407-413.
- Stephens, S. R., Alloway, B. J., Carter, J. E., & Parker, A. (2001). Towards the characterisation of heavy metals in dredged canal sediments and an appreciation of 'availability': two examples from the UK. *Environmental Pollution*, 113, 395–401.
- Sun, Y., Li, Y., Xu, Y., Liang, X., Wang, L., (2015). In situ stabilization remediation of cadmium (Cd) and lead (Pb) co-contaminated paddy soil using bentonite. *Appl. Clay Sci.* 105-106, 200–206.
- Suraj, G., Iyer, C. S. P., & Lalithambika, M. (1998). Adsorption of cadmium and copper by modified kaolinites. *Applied Clay Science*, 13(4), 293-306.
- Sutherland, R. A. (2002). Comparison between non-residual Al, Co, Cu, Fe, Mn, Ni, Pb and Zn released by a three-step sequential extraction procedure and a dilute hydrochloric acid leach for soil and road deposited sediment. *Applied Geochemistry*, 17(4), 353-365.
- Taneez, M., Hurel, C., Mady, F., & Francour, P. (2018). Capping of marine sediments with valuable industrial by-products: Evaluation of inorganic pollutants immobilization. *Environmental Pollution*, 239, 714-721.
- Teng, Y., Wu, J., Lu, S., Wang, Y., Jiao, X., Song, L., (2014). Soil and soil environmental quality monitoring in China: a review. *Environ. Int.* 69, 177–199.
- Tessier, A., Campbell, P. G., & Bisson, M. (1979). Sequential extraction procedure for the speciation of particulate trace metals. *Analytical chemistry*, 51(7), 844-851.
- Thibodeaux, L. J. and K. T. Duckworth (2001). "The effectiveness of environmental dredging: A study of three sites." *Remediation Journal* 11(3): 5-33.

- Thomas, R. P., Ure, A. M., Davidson, C. M., Littlejohn, D., Rauret, G., Rubio, R., & López-Sánchez, J. F. (1994). Three-stage sequential extraction procedure for the determination of metals in river sediments. *Analytica Chimica Acta*, 286(3), 423-429.
- Tick, G.R., Harvell, J.R., Murgulet, D., (2015). Intermediate-scale investigation of enhanced-solubilization agents on the dissolution and removal of a multicomponent dense nonaqueous phase liquid (DNAPL) source. *Water, Air, Soil Pollut.* 226 (11).
- Tokaloğlu, Ş., Kartal, Ş., & Elci, L. (2000). Determination of heavy metals and their speciation in lake sediments by flame atomic absorption spectrometry after a four-stage sequential extraction procedure. *Analytica Chimica Acta*, 413(1-2), 33-40.
- Tomašević, D. D., Kozma, G., Kerkez, D. V., Dalmacija, B. D., Dalmacija, M. B., Bečelić-Tomin, M. R., & Rončević, S. (2014). Toxic metal immobilization in contaminated sediment using bentonite-and kaolinite-supported nano zero-valent iron. *Journal of nanoparticle research*, 16(8), 2548.
- Tomaszewski JE, Werner D, Luthy RG (2007) Activated carbon amendment as a treatment for residual DDT in sediment from a superfund site in San Francisco Bay, Richmond, California, USA. *Environ Toxicol Chem* 26:2143–2150.
- Tomaszewski, J. E., Smithenry, D. W., Cho, Y. M., Luthy, R. G., Lowry, G. V., Reible, D., & Macková M. (2006). Treatment and containment of contaminated sediments. In *Assessment and Remediation of Contaminated Sediments*(pp. 137-178). Springer, Dordrecht.
- Triplett Kingston, J.L., Dahlen, P.R., Johnson, P.C., (2012). Assessment of groundwater quality improvements and mass discharge reductions at five in situ electrical resistance heating remediation sites. *Groundwater Monitoring & Remediation* 32 (3),41–51.
- Truitt, C. L. (1987). Engineering Considerations for Capping Subaqueous Dredged Material Deposits--Background and Preliminary Planing, DTIC Document.

- Tseng, R. L., Wu, F. C., & Juang, R. S. (2003). Liquid-phase adsorption of dyes and phenols using pinewood-based activated carbons. *Carbon*, 41(3), 487-495.
- Turan, P., Doğan, M., & Alkan, M. (2007). Uptake of trivalent chromium ions from aqueous solutions using kaolinite. *Journal of hazardous materials*, 148(1-2), 56-63.
- U.S. Environmental Protection Agency. (1994). "ARCS Remediation Guidance Document." EPA 905-R94-003. Great Lakes National Program Office, Chicago, IL.
- U.S. EPA. (1992). Framework for ecological risk assessment. Risk Assessment Forum. (EPA/505/2-90/001). Washington, DC: US EPA.
- U.S. EPA. (2007c). Chapter 3: Environmental chemistry, transport and fate framework for metals risk assessment. Washington, DC: US EPA.
- U.S. EPA. (1991). Sediment quality guidelines. Draft report. EPA Region V Chicago IL.
- Uddin, M. K. (2017). A review on the adsorption of heavy metals by clay minerals, with special focus on the past decade. *Chemical Engineering Journal*, 308, 438-462.
- Unuabonah, E. I., & Adebawale, K. O. (2009). Optimization of kinetic data for two-stage batch adsorption of Pb (II) ions onto tripolyphosphate-modified kaolinite clay. *Journal of Chemical Technology & Biotechnology*, 84(11), 1726-1735.
- Ure AM, Davidson CM, Thomas RP (1995) Single and sequential extraction schemes For Trace metal speciation in soil and sediment. *Tech and Instru in Anal Chem* 17: 505-523.
- Ure, A. M., & Davidson, C. M. (1995). Introduction to speciation. *Chemical speciation in the environment*, 1-5.
- Ure, A.M, Quevauviller V, Muntau H, Griepink B (1993) Speciation of heavy metals in solids and harmonization of extraction techniques undertaken under the auspices of the BCR of the Commission of the European Communities. *Int J Of Environ Anal Chem* 51: 135.

- USACE/USEPA. (2004). Evaluating Environmental Effects of Dredged Material Management Alternatives - A Technical Framework. EPA842-B-92-008. USEPA and USACE, Washington, DC, USA.
- USEPA. (2005a). Contaminated Sediment Remediation Guidance for Hazardous Waste Sites. EPA-540-R-05-012. USEPA Office of Solid Waste and Emergency Response, Washington, DC, USA.
- USEPA. (2007). Demonstration of the AquaBlok® sediment capping technology, Innovative technology evaluation report, SITE program. EPA/540/R-07/008. September 2007.
- USEPA. (2013). Use of Amendments for In Situ Remediation at Superfund Sediment Sites. Office of Superfund Remediation and Technology Innovation. April 2013. 61 pages.
- Usman, M., Faure, P., Ruby, C., Hanna, K., (2012). Remediation of PAH-contaminated soils by magnetite catalyzed Fenton-like oxidation. *Appl. Catal. B Environ.* 117-118, 10–17.
- Usman, M., Hanna, K., Haderlein, S., (2016). Fenton oxidation to remediate PAHs in contaminated soils: a critical review of major limitations and counter-strategies. *Sci. Total Environ.* 569-570, 179–190.
- Valaskova, M., & Martynkov á G. S. (Eds.). (2012). *Clay minerals in nature: their characterization, modification and application*. BoD–Books on Demand.
- Vasconcelos, I. F., Haack, E. A., Maurice, P. A., & Bunker, B. A. (2008). EXAFS analysis of cadmium (II) adsorption to kaolinite. *Chemical Geology*, 249(3-4), 237-249.
- Velimirovic, M., Tosco, T., Uyttebroek, M., Luna, M., Gastone, F., De Boer, C., & Braun, J. (2014). Field assessment of guar gum stabilized microscale zerovalent iron particles for in-situ remediation of 1, 1, 1-trichloroethane. *Journal of contaminant hydrology*, 164, 88-99.
- Vhahangwele, M., & Mugera, G. W. (2015). The potential of ball-milled South African bentonite clay for attenuation of heavy metals from acidic wastewaters: Simultaneous sorption of Co^{2+} , Cu^{2+} , Ni^{2+} , Pb^{2+} , and Zn^{2+} ions. *Journal of Environmental Chemical Engineering*, 3(4), 2416-2425.

- Vigliotta, G., Matrella, S., Cicatelli, A., Guarino, F., Castiglione, S., (2016). Effects of heavy metals and chelants on phytoremediation capacity and on rhizobacterial communities of maize. *J. Environ. Manag.* 179, 93–102.
- Violante, A., Cozzolino, V., Perelomov, L., Caporale, A. G., & Pigna, M. (2010). Mobility and bioavailability of heavy metals and metalloids in soil environments. *J. Soil Sci. Plan. Nutr.*, 10, 268-292.
- Wang, A. O., Ptacek, C. J., Blowes, D. W., Gibson, B. D., Landis, R. C., Dyer, J. A., & Ma, J. (2019). Application of hardwood biochar as a reactive capping mat to stabilize mercury derived from contaminated floodplain soil and riverbank sediments. *Science of The Total Environment*, 652, 549-561.
- Wang, X. S., & Qin, Y. (2007). Leaching characteristics of heavy metals and As from two urban roadside soils. *Environmental monitoring and assessment*, 132(1-3), 83-92.
- Washington Department of Ecology, (1995). Sediment Management Standards. Chapter 173204, Washington Administrative Code, amended December, 1995. In Long E. R.,
- Wilson, I. (2007). Applied Clay Mineralogy. Occurrences, processing and application of kaolins, bentonite, palygorskite-sepiolite, and common clays. Haydn H. Murray. Developments in Clay Science, volume 2, Elsevier Science, Amsterdam, 2007, 180+ viii pp. ISBN-13: 978-0-444-51701-2, ISBN-10: 0-444-51701-4.
- Wilson, I. R. (1998). The constitution, evaluation and ceramic properties of ball clays. *Cerâmica*, 44(287-288), 88-117.
- Wisconsin Department of Natural Resources. (2003). Consensus based sediment quality guideline. Recommendation for use and application. Department of interior, Washington D.C.20240 PP 17
- Worch, E. (2012). *Adsorption technology in water treatment: fundamentals, processes, and modeling*: Walter de Gruyter.
- Wu FC, Tseng RL, Juang RS (2009) Initial behavior of intraparticle diffusion model used in the description of adsorption kinetics. *Chem Eng J* 153:1–8
- Wu, F. C., Tseng, R. L., & Juang, R. S. (2002). Adsorption of dyes and humic acid from water using chitosan-encapsulated activated carbon. *Journal of*

Chemical Technology & Biotechnology: International Research in Process, Environmental & Clean Technology, 77(11), 1269-1279.

- Wu, M.Z., Reynolds, D.A., Fourie, A., Prommer, H., Thomas, D.G., (2012). Electrokinetic in situ oxidation remediation: assessment of parameter sensitivities and the influence of aquifer heterogeneity on remediation efficiency. *J. Contam. Hydrol.* 136-137, 72–85.
- Wu, P., Zhang, Q., Dai, Y., Zhu, N., Dang, Z., Li, P., & Wang, X. (2011). Adsorption of Cu (II), Cd (II) and Cr (III) ions from aqueous solutions on humic acid modified Ca-montmorillonite. *Geoderma*, 164(3-4), 215-219.
- Wuana, R. A., & Okieimen, F. E. (2011). Heavy metals in contaminated soils: a review of sources, chemistry, risks and best available strategies for remediation. *Isrn Ecology*, 2011.
- Li, X., Shen, Z., Wai, O. W., & Li, Y. S. (2001). Chemical forms of Pb, Zn and Cu in the sediment profiles of the Pearl River Estuary. *Marine Pollution Bulletin*, 42(3), 215-223.
- Xu, J., Zhang, Y., Zhou, C., Guo, C., Wang, D., Du, P., & Meng, W. (2014). Distribution, sources and composition of antibiotics in sediment, overlying water and pore water from Taihu Lake, China. *Science of the Total Environment*, 497, 267-273.
- Xu, P., Zeng, G. M., Huang, D. L., Feng, C. L., Hu, S., Zhao, M. H., & Liu, Z. F. (2012). Use of iron oxide nanomaterials in wastewater treatment: a review. *Science of the total environment*, 424, 1-10.
- Yin K, Viana P, Zhao X, Rockne K A Monte Carlo simulation approach for active caps in mixed contaminant environments. In: *Proceedings of the Fourth International Conference on Remediation of Contaminated Sediments*, 2007
- Yu, R., Wang, S., Wang, D., Ke, J., Xing, X., Kumada, N., & Kinomura, N. (2008). Removal of Cd²⁺ from aqueous solution with carbon modified aluminum-pillared montmorillonite. *Catalysis Today*, 139(1-2), 135-139.
- Yuan CG, Shi JB, He B, Liu JF, Liang LN, et al. (2004) Speciation of heavy metals in marine sediments from the East China Sea by ICP-MS with sequential extraction. *Environ Int* 30: 769-783.

- Yuan, G. D., Theng, B. K. G., Churchman, G. J., & Gates, W. P. (2013). Clays and clay minerals for pollution control. In *Developments in clay science* (Vol. 5, pp. 587-644). Elsevier.
- Mester, Z., C. Cremisini, E. Ghiara and R. Morabito, Anal. Ch im. (1998) Acta, 359, 133-142
- Zahrim, A. Y., Ricky, L. N. S., Hilal, N., & Tamrin, K. F. (2017). Cadmium Recovery from Synthetic Solution using Agricultural Waste Fibers. *Indian Journal of Science and Technology*, 10(6), 1–5.
- Zarull, M. A., J. H. Hartig and L. Maynard (1999). "Ecological benefits of contaminated sediment remediation in the Great Lakes basin."
- Zeller C, Cushing B (2006) Panel discussion: remedy effectiveness: what works, what doesn't? *Integr Environ Assess Manag* 2:75–79.
- Zeman AJ (1994) Subaqueous capping of very soft contaminated sediments. *Can Geotech J* 31:570–577. Lampert DJ, Sarchet WV, Reible DD (2011) Assessing the effectiveness of thin-layer sand caps for contaminated sediment management through passive sampling. *Environ Sci Technol* 45:8437–8443.
- Zeng, G., Song, B., Gong, J., Chang, Y., & Jiang, Y. (2016). Antibacterial properties and mechanism of graphene oxide-silver nanocomposites as bactericidal agents for water disinfection. *Archives of biochemistry and biophysics*, 604, 167-176.
- Zeng, G.M., Chen, M., Zeng, Z.T., (2013a). Risks of neonicotinoid pesticides. *Science* 340 (6139), 1403.
- Zhang, C., Nie, S., Liang, J., Zeng, G., Wu, H., Hua, S., & Xiang, H. (2016). Effects of heavy metals and soil physicochemical properties on wetland soil microbial biomass and bacterial community structure. *Science of the Total Environment*, 557, 785-790.
- Zhang, C., Zhu, M. Y., Zeng, G. M., Yu, Z. G., Cui, F., Yang, Z. Z., & Shen, L. Q. (2016). Active capping technology: a new environmental remediation of contaminated sediment. *Environmental Science and Pollution Research*, 23(5), 4370-4386.
- Zhang, S., Tian, K., Jiang, S. F., & Jiang, H. (2017). Preventing the Release of Cu²⁺ and 4-CP from Contaminated Sediments by Employing a Biochar

- Capping Treatment. *Industrial & Engineering Chemistry Research*, 56(27), 7730-7738.
- Zhang, X., Wang, H., He, L., Lu, K., Sarmah, A., Li, J. & Huang, H. (2013). Using biochar for remediation of soils contaminated with heavy metals and organic pollutants. *Environmental Science and Pollution Research*, 20(12), 8472-8483.
- Zhang, Y., Dong, X., Jiang, Z., Cao, B., Ge, S., Hu, M., (2013a). Assessment of the ecological security of immobilized enzyme remediation process with biological indicators of soil health. *Environ. Sci. Pollut. Res.* 20 (8), 5773–5780.
- Zhang, Y., Zeng, G.M., Tang, L., Huang, D.L., Jiang, X.Y., Chen, Y.N., (2007). A hydroquinone biosensor using modified core-shell magnetic nanoparticles supported on carbon paste electrode. *Biosens. Bioelectron.* 22 (9 –10), 2121–2126.
- Zhou, Q., Zhang, L., Chen, J., Xu, B., Chu, G., Chen, J., (2016). Performance and microbial analysis of two different inocula for the removal of chlorobenzene in biotrickling filters. *Chem. Eng. J.* 284, 174–181.
- Zhu L, Chen B, ShenX (2000) Sorption of phenol, p-nitrophenol, and aniline to dual-cation organobentonites from water. *Environmental Science & Technology* 34, 468–475.
- Zhu, J., Zhang, P., Wang, Y., Wen, K., Su, X., Zhu, R., & Xi, Y. (2018). Effect of acid activation of palygorskite on their toluene adsorption behaviors. *Applied Clay Science*, 159, 60-67.
- Zhu, T., Cao, T., Ni, L., He, L., Yi, C., Yuan, C., & Xie, P. (2016). Improvement of water quality by sediment capping and re-vegetation with *Vallisneria spiralis* L.: A short-term investigation using an in situ enclosure experiment in Lake Erhai, China. *Ecological engineering*, 86, 113-119.
- Zimmerman JR, Werner D, Ghosh U, Millward RN, Bridges TS, Luthy RG (2005) Effects of dose and particle size on activated carbon treatment to sequester polychlorinated biphenyls and polycyclic aromatic hydrocarbons in marine sediments. *Environ Toxicol Chem* 24:1594–1601.

Zoumis, T., Schmidt, A., Grigorova, L., & Calmano, W. (2001). Contaminants in sediments: remobilisation and demobilisation. *Science of the total environment*, 266(1-3), 195-202.

